

1 LOCATION OF WATER WELL: County: Kingman Fraction: SE 1/4 SE 1/4 NE 1/4 Section Number: 17 Township Number: T 28 S Range Number: R 10 E

Distance and direction from nearest town or city street address of well if located within city?  
2 1/2 S Cunningham

2 WATER WELL OWNER: Tom Strohl  
RR#, St. Address, Box #: Cunningham, Kas 67035  
City, State, ZIP Code: Cunningham, Kas 67035 Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 108 ft. ELEVATION: 6-7-82  
Depth(s) Groundwater Encountered: 47 ft. 2. 87 ft. 3. 108 ft.  
WELL'S STATIC WATER LEVEL: 47 ft. below land surface measured on mo/day/yr  
Pump test data: Well water was 2.0 gpm: Well water was 108 ft. after 6-7-82 hours pumping 2.0 gpm  
Bore Hole Diameter: 9 in. to 108 ft., and 108 in. to 108 ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter: 5 in. to 16 1/2 ft. Dia. 16 1/2 in. to 16 1/2 ft. Dia. 16 1/2 in. to 16 1/2 ft. Dia. 16 1/2 in. to 16 1/2 ft. Dia.  
Casing height above land surface: 16 1/2 in., weight 16 1/2 lbs./ft. Wall thickness or gauge No. 265  
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 93 ft. to 108 ft., From 93 ft. to 108 ft., From 93 ft. to 108 ft., From 93 ft. to 108 ft.  
GRAVEL PACK INTERVALS: From 13 ft. to 108 ft., From 13 ft. to 108 ft., From 13 ft. to 108 ft., From 13 ft. to 108 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.  
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage  
Direction from well? S How many feet? 225

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Soil			
4	15	Clay			
15	35	Fine Sand			
35	50	Coarse Sand			
50	61	Fine Sand			
61	87	Clay			
87	108	Med Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-8-82 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 6-8-82  
under the business name of Lyman Bros by (signature) Richard Lyman  
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.