

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County PRATT.	Fraction NE 1/4 SE 1/4	Section number 20	Township number T 28 S	Range number R 11 W
2. Distance and direction from nearest town or city:		3. Owner of well		3. Owner of well		
Street address of well location if in city:		R.R. or street		City, state, zip code:		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 28 in. Completion date		
N		Sketch map:		Well depth 194 ft. July 2, 1975		
W		Sketch map:		7. Cable tool Rotary Driven Dug		
E		Sketch map:		Hollow rod Jetted Bored <input checked="" type="checkbox"/> Reverse rotary		
S		Sketch map:		8. Use: Domestic Public supply Industry		
1 Mile		Sketch map:		<input checked="" type="checkbox"/> Irrigation Air conditioning Stock		
1 Mile		Sketch map:		Lawn Oil field water Other		
5. Type and color of material		From		To		9. Casing: Material Height: Above or below
Clay		0		12		Threaded Welded Surface 12 in.
Sand		12		15		RMP PVC Weight 30 lbs./ft.
Clay		15		20		Dia. 16 in. to 142 ft. depth Wall Thickness inches or
Sand		20		30		Dia. in. to ft. depth gage No. 3/4
Clay		30		40		10. Screen: Manufacturer's name
Sand		40		96		Type Dia. 16
Sand-hard, coarse, cemented		96		98		Slot/gauze 3/16 Length 62
Sand		98		105		Set between 142 ft. and 194 ft.
Cal g		105		125		Gravel pack? yes Size range of material 1/8-1/4
Sand		125		127		11. Static water level: mo./day/yr.
Sand-cemented		127		130		64 ft. below land surface Date 6/28/75
Med. sand, some clay		130		153		12. Pumping level below land surfaces:
Clay		153		160		101 ft. after 1 hrs. pumping 1200 g.p.m.
Fine to Med. sand		160		194		89 ft. after 12 hrs. pumping 800 g.p.m.
						Estimated maximum yield 1350 g.p.m.
						13. Water sample submitted: mo./day/yr.
						Yes <input checked="" type="checkbox"/> No Date
						14. Well head completion:
						Pitless adapter 12 inches above grade
						15. Well grouted yes
						With: Neat cement <input checked="" type="checkbox"/> Bentonite Concrete
						Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination:
						ft. Direction Type
						Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No
						17. Pump: Not installed
						Manufacturer's name Western Land Roller
						Model number 12 CM HP 64 Volts
						Length of drop pipe 110 ft. capacity 800 g.p.m.
						Type:
						Submersible <input checked="" type="checkbox"/> Turbine
						Jet Reciprocating
						Centrifugal Other
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography:				This well was drilled under my jurisdiction and this report		
Hill				is true to the best of my knowledge and belief.		
Slope				Darling Drilling Co 189		
<input checked="" type="checkbox"/> Upland				Business name License No.		
Valley				Address 1211 W. 4th Hutchinson, KS		
				Signed Donald J. Darling July 1975		
				Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5