TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 160 ft. to 180 ft., From ft. to GRAVEL PACK INTERVALS: From 1.0 ft. to 1.80 ft., From ft. to 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Distance and direction from nearest town or city street address of well if located within city? 5 s, 2 1/2 W of Cummingham, Kansas DYCH C
WATER WELL OWNER: Bildon Dysle Heartland Drilling Dysle No. 1–25 BR#, 8t. Address, Box #: Route 4, One Main Place Board of Agriculture, Division of Water Resource (IX), State, 219 Code Pratt, Ks. 67124, Wichita, Ks. 67202 Application Number: T84,–392 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
RR#, St. Address, Box #: ROute 4
RR#, St. Address, Box #: ROute 4
DEPTH OF COMPLETED WELL 180 ft. ELEVATION: Unknown Depth(s) Groundwater Encountered 1.65 ft. 2 ft. 3 ft.
Depth(s) Groundwater Encountered 1.68 ft. 2 ft. 3 ft. 3 ft. 4 WELL'S STATIC WATER LEVEL 68 ft. below land surface measured on mor/day/yr 7/14/84. Pump test data: Well water was ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. and in. to 180 ft.
WELL'S STATIC WATER LEVEL 68 ft. below land surface measured on mo/day/yr 7/14/84. Pump test data: Well water was ft. after hours pumping gp Est. Yield 60 gpm: Well water was ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 8 in. to 180 ft. after hours pumping gp Bore Hole Diameter 9 Diam
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded. Blank casing diameter 5 in to 160 ft., Dia in to ft., Dia in to ft., Dia in to ft., From ft.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 16.0 ft. to 180 ft., From ft. to GRAVEL PACK INTERVALS: From 1.0 ft. to 180 ft., From ft. to GRAVEL PACK INTERVALS: From 1.0 ft. to 180 ft., From ft. to 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft., From ft. to 10 Livestock pens 14 Abandoned water well
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From. 160 ft. to 180 ft., From. ft. to From. ft. to 10 ft. to ft. to GRAVEL PACK INTERVALS: From. 10 ft. to 180 ft., From. ft. from. ft. to 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From. 0 ft., From. ft. to ft. to What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From. 160 ft. to 180 ft., From ft. to ft., From f
2 Louvered shutter
SCREEN-PERFORATED INTERVALS: From. 160 ft. to 180 ft., From ft. to ft., From ft. to From ft. to ft., From ft. ft., From ft. ft., From ft. ft., From ft. ft., From
From
GRAVEL PACK INTERVALS: From. 1.0 ft. to 180
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From
Grout Intervals: From
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? South How many feet? 60
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
15 Clay
15 175 Sand and Gravel
175 180 Shale
175 180 Shale
175 180 Shale
175 180 Shale
175 180 Shale
175 180 Shale
175 180 Shale
175 180 Shale
175 180 Shale
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and wa
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and watcompleted on (mo/day/year) 7/14/84
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/1½/8½. and this record is true to the best of my knowledge and belief, Kansa water Well Contractor's License No. 186 This Water Well Record was completed on (mo(day/yr)
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and watcompleted on (mo/day/year) 7/14/84