USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215



Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

County	Fraction	Section	number	Township number	Range number	]
1. Location of well: PRATT	SE1/4 NW1/4 NW1/4	2	<del>```</del>		5 R 12W EN	1
2. Distance and direction from nearest town or city: 35 7E 0F  3. Owner of well: JOHN MEGAFFIN  R.R. or street:					IN	
Street address of well location if in city:  PROTT, K5  City, state, zip code: PRATT, K5						
4. Locate with "X" in section below: Sketch map:			'	6. Bore hole dia. 30 Well depth 206 ft.	in. Completion date	
WATER WOLL				7 Cable tool _ Rota		1
WAT 32 WEC				Hollow rod Jette	edBored X Reverse rotary	1
w i i i i				8. Use: Domestic	Public supply Industry Air conditioning Stock	
SW SE					Oil field water Other	-
<u> </u>				9. Casing: Material Height: Above or below Threaded Welded X Surface 12 in.		
S DRAINA GE			RMPPVCWeightlbs./ft. Dia 6 in. to 65 ft. depth Wall Thickness: inches or			
5. Type and color of material	•	From	То	Dia in. to ft. d	epth gage No	-
SeiL			3	10. Screen: Manufacturer' WA Block	s name	
				Type PREFLO Slot/gauze VQ	Dia	
CLAY, TANGWHITE WITHIN SAND STREAK			31	Set between	ft. andft. . andft.	
CLAY, SANDY TAN			59	Gravel pack? YES Size	range of material 1/4 - 1/2	1
SMID, FINE TO COARSE & MED GRAVEL			70	11. Static water level:ft. below land:	mo./day/yr.surface Date <u>  APRIC 77</u>	
CLAY, GRAY			83	12. Pumping level below to	and surfaces:	
SAND, FINE TO GARSE & MED GRAVEL			104	6 ft. after 1/2	hrs. pumping 263 g.p.m.	
Clay, WHITE			106	Estimated maximum yield	f: g.p.m. mo./day/yr.	
SAND, FINE TO COARSE & MOD GRAVEL			145	Yes No  14. Well head completion:	Date	1
CLAY, YELLOW GRAY		106		Pitless adapter	12 Inches above grade	
SAUD. FLUETO CORSE & MED CRAVEL			100	15. Well grouted? YES With: Neat cement	Bentonite Concrete	1
			104	Depth: From ft. f		0
CLY, IAN WY SOND STREAKS			184	II Direction _	ble contamination:	
CLIY, GRAY W/ FIND S	MD	184	195	Well disinfected upon comp 17. Pump:	oletion? X Yes No	
SWD, FINE			205	Manufacturer's name		"
CLAY, GRAY			216	Length of drop pipe 14	of ft. capacity 800 g.p.m.	8
SAND, FINE TO COASS & MED GRAVEL (DIDTY)			223	Type: Submersible	X. Turbine	
SHALE, RED (Use a second	sheet if needed)	223	240	Jet Centrifugal	Reciprocating Other	1 × 1
18. Elevation: 19. Remarks: 28752			20. Water well contractor!		ાં હ	
1850 5'X10' CONCRETE SLAB			This well was drilled under is true to the best of my known	my jurisdiction and this report owledge and belief.	≥ M	
Topography: Hill SURFACE				Business name	\$ pump 325	l –
				Address 12/5 73	Kok PRITT	\z  \ge
Valley Z 8 12 40 ND X				Signed Authorized re	apresentative April 77	2 2