

1 LOCATION OF WATER WELL		Fraction 8W 1/4 SE 1/4	Section, Number 36	Township Number T 28 S	Range Number R 12 E/W
County: Pratt					
Distance and direction from nearest town or city? 6 miles north of West Jabel Kana			Street address of well if located within city?		
2 WATER WELL OWNER: Roger Haus					
RR#, St. Address, Box #			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code Wheat Jabel Kana 67065			Application Number:		
3 DEPTH OF COMPLETED WELL 100 ft. Bore Hole Diameter 3 in. to 3 ft., and 3 in. to 3 ft.					
Well Water to be used as:					
☒ Domestic 3 Feedlot ☐ Irrigation 4 Industrial		5 Public water supply 6 Oil field water supply 7 Lawn and garden only		8 Air conditioning 9 Dewatering 10 Observation well	
11 Injection well 12 Other (Specify below)					
Well's static water level 65 ft. below land surface measured on 12 month 8 day 81 year					
Pump Test Data NK : Well water was 12 ft. after 8 hours pumping 81 gpm					
Est. Yield 12 gpm: Well water was 12 ft. after 8 hours pumping 81 gpm					
4 TYPE OF BLANK CASING USED:					
☐ Steel 3 RMP (SR) ☒ PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (specify below) Casing Joints: Glued ☒ Clamped ☐ Welded ☐ Threaded ☐	
Blank casing dia 5 in. to 5 ft., Dia 5 in. to 5 ft., Dia 5 in. to 5 ft.					
Casing height above land surface 2 feet in., weight 14 lbs./ft. Wall thickness or gauge No 14					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel 3 Stainless steel ☐ Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile		☒ PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)	
Screen or Perforation Openings Are:					
☒ Continuous slot ☐ Louvered shutter		3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)	
Screen-Perforation Dia 5 in. to 100 ft., Dia 5 in. to 100 ft., Dia 5 in. to 100 ft.					
Screen-Perforated Intervals: From 80 ft. to 100 ft., From 80 ft. to 100 ft., From 80 ft. to 100 ft.					
Gravel Pack Intervals: From 10 ft. to 100 ft., From 10 ft. to 100 ft., From 10 ft. to 100 ft.					
5 GROUT MATERIAL: ☒ Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grouted Intervals: From 1 ft. to 10 ft., From 1 ft. to 10 ft., From 1 ft. to 10 ft.					
What is the nearest source of possible contamination:					
☒ Septic tank 2 Sewer lines 3 Lateral lines		4 Cess pool 5 Seepage pit 6 Pit privy		7 Sewage lagoon 8 Feed yard 9 Livestock pens 10 Fuel storage 11 Fertilizer storage 12 Insecticide storage 13 Watertight sewer lines 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well East How many feet 200 ? Water Well Disinfected? Yes ☒ No ☐					
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, date sample was submitted 12 month 8 day 81 year: Pump Installed? Yes ☐ No ☒					
If Yes: Pump Manufacturer's name STAY Rite Model No. 8500 HP 1/2 Volts 230					
Depth of Pump Intake 75 ft. Pumps Capacity rated at 8 Gallon gal./min.					
Type of pump: ☒ Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other					
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on Dec 12 month 8 day 81 year					
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 226					
This Water Well Record was completed on 12 month 14 day 81 year under the business name of Neber Well Service by (signature) Leon G. Neber					
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
		TOP Soil 1			
		10 10 Sand			
		20 20 White Shp.			
		30 30 Clay Brown			
		40 40 Sand, fine			
		50 50 Sand, Brown			
		60 60 Clay			
		70 70 Sand, fine			
		80 80 Sand, coarse			
		90 90 Coarse gravel			
ELEVATION: 100		Carthage atal Dept of Well 100 feet clay bottom			
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft.					

OFFICE USE ONLY

T

28

R

12

E

36

SEC

SW 1/4

SE 1/4

1/4

1/4

1/4

1/4