

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>PRATT</u>	<u>SW 1/4 NW 1/4 SW 1/4</u>	<u>3</u>	T <u>28</u> <u>S</u>	R <u>13</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

HWY 281 * SOUTHERN Railroad Tracks Pratt Kansas 671242 WATER WELL OWNER: AMPRIDERR#, St. Address, Box # : 916 S. MAIN STREET

Board of Agriculture, Division of Water Resources

City, State, ZIP Code : PRATT Kansas 67124

Application Number:

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1852.28

AN "X" IN SECTION BOX:

Depth(s) Groundwater Encountered 1. 20 ft. 2. 13 ft. 3. 11/8/01 ft.WELL'S STATIC WATER LEVEL 1839.42 ft. below land surface measured on mo/day/yrPump test data: Well water was 8.25 ft. after 20 hours pumping 11/8/01 gpmEst. Yield 8.25 gpm: Well water was 20 ft. after 20 hours pumping 11/8/01 gpmBore Hole Diameter 8.25 in. to 20 ft., and 20 in. to 20 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes No X5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Welded Clamped Threaded

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)

2 PVC 4 ABS 7 Fiberglass 2 PVC 10 Asbestos-cementBlank casing diameter 10.206 in. to 10 ft., Dia 10.206 in. to 10 ft., Dia 10.206 in. to 10 ft.Casing height above land surface 2.88 in., weight 0.8 lbs./ft. Wall thickness or gauge No. SCH 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 2 Mill slot 6 Wire wrapped 9 Drilled holes2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 10 ft.SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From 10 ft. to 20 ft., From 10 ft. to 20 ft.GRAVEL PACK INTERVALS: From 8 ft. to 20 ft., From 8 ft. to 20 ft., From 8 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 1 ft. to 8 ft., From 1 ft. to 8 ft., From 1 ft. to 8 ft., From 1 ft. to 8 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) LUST SITE

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0' 0.5' Concrete0.5' 6' Clay, Black, silty dense, low6' 20' Plasticity /cl6' 20' Clay, Brown, silty dense,6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl6' 20' low plasticity /cl7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and wascompleted on (mo/day/year) 9/25/01 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's Licence No. 594 This Water Well Record was completed on (mo/day/yr) 11/27/04under the business name of Coranco Great Plains by (signature) Dennis J. Sprague