WATER WELL RECORD			Form WWC-5		Division of Wate	er Resources App. No	). L
	LOCATION County: Pra	OF WATER WELL:	Fraction NE ¼ NE ¼ NE	¼ NW ¼	Section Number 3		Range Number R 13 ☐E [7]W
:	Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning System (GPS) information:			
1	from nearest town or intersection: If at owner's address, check here .			Latitude: .37.64574(in decimal degrees)			
	701 East 1st, Pratt, KS 67124			Longitude: 98.73154 (in decimal degrees)			
					Elevation: .1881.59 Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27		
2	WATER WELL OWNER: KDHE - BER				Collection Method:		
	RR#, Street Address, Box #: 1000 SW Jackson. Suite 410			GPS unit (Make/Model:)			
City, State, ZIP Code : Topeka,			S 66612-1367 □ Digital Map/Photo, □ Topographic Map, □ Lan			Map, ☐ Land Survey	
2 1	Est. Accuracy:						
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 57.5 ft.						
	SECTION BOX: Depth(s) Groundwater Encountered (1).45						
N WELL'S STATIC WATER LEVELNMft. below land surface measured on mo/day/yr							y/yr
Pump test data: Well water wasft. after hours pumping							ing gpm
	EST. YIELDgpm. Well water wasft. afterhours pumpinggpm  Bore Hole Diameter 8.25in. to .57.5ft., andin. toft.  WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
W							
l							
ľ	SW  SE     Domestic   Feedlot   Oil field water supply   Dewatering   Other (Specify below)     Irrigation   Industrial   Domestic-lawn & garden   Monitoring well						
L	Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No						
	S If yes, mo/day/yr sample was submitted						
		1	fected?  Yes  1				
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .2 in. to .55 ft., Diameter in. to							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
SCREEN-PERFORATED INTERVALS: From							
Fromft. toft. From							
GRAVEL PACK INTERVALS: From							
From							
6 GROUT MATERIAL: Neat cement Cement grout W Bentonite Other							
Grout Intervals: From .1							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)							
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well LUST Site  Direction from well							
FRO		LITHOLOG		FROM			GGING INTERVALS
0	1	Crushed Rock	IC EOG	TROM	TO EITHOLE	OG (cont.) of 1 Eo	JOING INTERVALS
1	19	Silty High Plasticity Clar	v/CH			-	
19	27	Fine to Medium Sand/S			ASW7	*****	
27	44	Silty Low Plasticity Clay			KDHE ID#	0051641	
44	57.5	Fine to Medium Sand/S	W				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged							
und	er mv jurisdi	ction and was completed or	(mo/dav/vear) 6/3/1	5 an	d this record is true:	to the best of my b	orea, or prugged nowledge and helief
under my jurisdiction and was completed on (mo/day/year) .6/3/15							
und	er the busine	ss name of Coranco Gre	eat Plains, Inc	• • • • • • • • • • • • • • • • • • • •	by (signature)	11/11	
INS	TRUCTIONS:	Use typewriter or ball point pen	PLEASE PRESS FIRMLY	and PRINT cle	arly. Please fill in blank	and check the correct a	inswers. Send one copy to
Te		epartment of Health and Environm 5-5524. Send one copy to WATE					

http://www.kdheks.gov/waterwell/index.html