WATER WELL R		WWC-5	Divi	sion of Water		
	Correction Change in Well Use		Resources App. No.			Well ID
1 LOCATION OF WATER WELL: Fraction		•				
County: YRATT 45E 4NW 4A				6	T 28 S	R /3 □ E / X W
2 WELL OWNER: L	ast Name: Rundel	1 First: Kenny			ere well is located (i	
1 Dusiness. The public of the						
Address:						
City: PRATT	State: 🖈	5 ZIP: 67124	pues		To well	
3 LOCATE WELL	4 DEPTH OF CO	MPLETED WELL:	80 A	5 Latitudo		(4
WITH "X" IN	Depth(s) Groundwate					
SECTION BOX:	2) ft.		Datum: WGS 84 NAD 83 NAD 27			
IN .	WELL'S STATIC W	ft.	Source for Latitude/Longitude:			
ا ابر ا ا	☐ below land surfa	/-yr)	GPS (unit make/model:			
NW NE	above land surfa		(
	Pump test data: Well		☐ Land Survey ☐ Topographic Map			
W	•	after hours pumping gpm Well water was ft.			e Mapper:	•••••
SW SE	after hours pumping gpm					
	Estimated Yield:				☐ Ground Level ☐ TOC	
S	Bore Hole Diameter:	ft. and	Source:			
S Bore Hole Diameter: 10.36 in. to80 ft. and Source: Land Survey GPS Topographic Map in. to ft.						
7 WELL WATER TO BE USED AS:						
1. Domestic:						
☐ Household☐ Lawn & Garden			11. Test Hole: well ID			
Livestock			12. Geothermal: how many bores?			
2. Irrigation		D	a) Closed Loop Horizontal Vertical			
3. ☐ Feedlot	☐ Air Spa	Extraction	b) Open Loop Surface Discharge Inj. of Water			
4. Industrial	☐ Recovery ☐ Injection 13. ☐ Other (specify):					
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:						
Water well disinfected?	Yes 🔲 No		•			
8 TYPE OF CASING USED: ☐ Steel PVC ☐ Other CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☐ Threaded						
Casing diameter						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL: □ Steel □ Steel □ Fiberglass □ Other (Specify)						
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous Slot						
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)						
SCREEN-PERFORATED INTERVALS: From						
GRAVEL PACK INTERVALS: From						
9 GROUT MATERIAL: Neat cement Cement grout Dentonite Other Grout Intervals: From P. ft., From ft						
		ft., From	. ft. to	ft., From	ft. to	ft.
Nearest source of possible contamination: Septic Tank						
Sewer Lines	☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well					· ·
☐ Watertight Sewer Lin						
☐ Other (Specify) Direction from well? Distance from well?						
			vell? 7.7.			
10 FROM TO		OGIC LOG	FROM	TO LIT	THO. LOG (cont.) or P	LUGGING INTERVALS
0 12		<u>50:/</u>				
12 70 70 78 78 80	Fine Tan Sand					*****
70 78	Coarse Sand & gravel		+			
78 80	TAN CA					
	Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, \square reconstructed, or \square plugged						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 2-23.4 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No						
under the business name	mactor's License No.		SUR.	ord was comple	cica dei (mo-day ya	r) . 146.7.54
INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submittee \$3.00 for each constructed well along with one (white) copy to Kansas						
Department of Health and Environment Bureau of Water Geology Section 1000 SW Jackson St. Suite 420. Toneka Kansas 66612-1367. Telephone (785) 296-3565						

KSA 82a-1212

Revised 9/10/2012

Visit us at http://www.kdheks.gov/waterwell/index.html