

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pratt		SE 1/4 SE 1/4 NE 1/4	23	T 28 S	R 14 W EW
Distance and direction from nearest town or city street address of well if located within city? two east two and one half south of Cullison					
2 WATER WELL OWNER: Kent Smith		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : 87 NW 10		Application Number:			
City, State, ZIP Code : Pratt, 67124					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 82 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 10-9-02 ft.			
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 10-9-02			
		Pump test data: Well water was 10 gpm. Well water was 82 ft. after 10 hours pumping 10 gpm.			
		Est. Yield 10 gpm. Well water was 82 ft. after 10 hours pumping 10 gpm.			
		Bore Hole Diameter 9 in. to 82 ft. and 10 in. to 10 ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped. No			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile 11 Injection well			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) 12 Other (Specify below)			
Blank casing diameter 5 in. to 77 ft. Dia 17 in. to 250 lbs./ft. Wall thickness or gauge No. 250		7 Fiberglass 10 Asbestos-cement			
Casing height above land surface 17 in. weight 250 lbs./ft.		8 Saw cut 11 None (open hole)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		9 Other (specify below)			
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) ft.					
SCREEN-PERFORATED INTERVALS: From 77 ft. to 82 ft. From 82 ft. to 82 ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 82 ft. From 82 ft. to 82 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 82 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? none with in		How many feet? 100			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	sandy soil			
2	8	fine sand			
8	17	sand			
17	26	brown clay			
26	36	yellow sand			
36	42	red sand			
42	62	sand			
62	82	sand some medium			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 10-9-02 and this record is true to the best of my knowledge and belief, Kansas					
Water Well Contractor's Licence No. 140 This Water Well Record was completed on (mo/day/yr) 11-9-03					
under the business name of Ly an Inc. by (signature) W. Alan Lyman					