


LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: PRATT		C 1/4 S 1/2 SW 1/4 E 1/4	35	T 28 S	R 14 E (N)
Distance and direction from nearest town or city street address of well if located within city? PRATT 51/45 41/3W NORTHSIDE					
WATER WELL OWNER: D.R. LAUCK OIL CO. INC.		PERMIT S. OMO, RFD 2 PRATT, KS			
RR#, St. Address, Box #: 221 S. BROADWAY SUITE 400		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: WICHITA, KS 67202		Application Number: T83-211			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 130 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 85 ft. 2. 6-1-83 ft. 3. 6-1-83 ft.			
		WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 6-1-83			
		Pump test data: Well water was 7 ft. after 7 hours pumping 7 gpm			
		Est. Yield 7 gpm Well water was 7 ft. after 7 hours pumping 7 gpm			
		Bore Hole Diameter 7.78 in. to 130 ft. and 130 in. to 130 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XY Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below)		Threaded			
Blank casing diameter 5 in. to 110 ft. Dia 110 in. to 110 ft. Dia 110 in. to 110 ft.					
Casing height above land surface 12 in. weight 265 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1/8		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 12 None (open hole)					
SCREEN-PERFORATED INTERVALS: From 110 ft. to 130 ft. From 110 ft. to 130 ft. From 110 ft. to 130 ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 110 ft. From 10 ft. to 110 ft. From 10 ft. to 110 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft.					
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	SOIL			
5	15	CLAY			
15	70	DRY SAND			
70	85	CLAY			
85	130	GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-1-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 6-11-83 under the business name of REISER WATER WELL SERV. INC. by signature [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					