USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number		
1. Location of well:	Pratt	SE 1/4 SW 1/4 NW 1/4		10		т 28 s	R 14W	E/W	
2. Distance and dire	ection from nearest town or city: 3E	er of wel		illip Lunt	1				
Street address of well location if in city: Cullison  R.K. or street:  City, state, zip code:						ullison, Kansas 67124			
4. Locate with "X" in section below: Sketch map:				INAGE		6. Bore hole dia. 28 in. Completion date Well depth 172ft. 14 July 76			
X WATER W				NeLL		7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X_ Reverse rotary			
						8. Use: Domestic Public supply Industry X_ Irrigation Air conditioning Stock			
11         / 12 / 12 / 12 / 12 / 12 / 12						9. Casing: Material Ste		elow	
S S S S S S S S S S S S S S S S S S S						Threaded Welded Surface 12 in.   RMP PVC Weight lbs./ft.			
5. Type and color of material				From	То	Dia. 16 in. to 174. dep	th gage No. <u>• 18</u>	hes or	
Soil				0	2	10. Screen: Manufacturer's r W. A. Brown Type Freeflo			
Clay, Tan				2	46	Slot/Initial 1/8 Set between 132	Length 401	ft.	
Sand, Fine to coarse and fine gravel			46	70	Gravel pack? YES Size ra	and	ft.		
Clay, Gray and tan			70	80	11. Static water level:	face Date 1Jul	/day/yr. У 76		
Sand, fine to coarse and medium gravel			80	111	12. Pumping level below land	d surfaces: hrs. pumping 900	g.p.m.		
Sand, cemented and clay					119	ft. after I	1500	g.p.m. _g.p.m.	
Sand, fine to coarse				119	143	13. Water sample submitted: YesX_ No	mo.	/day/yr.	
Sand, fine to coarse & medium coarse gr				170	14. Well head completion:	12 Inches above	rade		
Clay, sandy tan and rock hard				170	186	15. Well grouted? VAS			k
Clay, sandy tan and sand and gravel			<b></b>	188	With: Neat cement _X Depth: From ft. to	BentoniteC 	concrete _	  V	
Shale, red			188	195	16. Nearest source of possible ft Direction			l~	
						Well disinfected upon comple 17. Pump:	tion? X Yes _	No	<b> </b>
					Manufacturer's name <u>F1</u>	Not installed OWAY	~	H	
•					Model number 12001 Length of drop pipe 140	_ HP <u>90</u> Vol _ ft. capacity <u>900</u>		<b>(</b> ₹)	
					Type: Submersible	X Turbine		,	
(Use a second sheet if needed)					Jet Centrifugal	Recipro	cating	, <b> </b> -	
18. Elevation:	earthen pad 2'thick x18'x30' long was					This well was drilled under m	y jurisdiction and this	report	C
Topography:	built around the well and a 5'x10'x1'					is true to the best of my knowledge and belief.  Central Well & Pump 325			K
Slope	ing the casing 3' above original ground					Business name License No.			SE
level						Sign Authorized rep	resentative 14 July	1776 E	<b>X</b>