

1 LOCATION OF WATER WELL: County: Pratt	Fraction NE 1/4 NE 1/4 NW 1/4	Section Number 25	Township Number T 28 S	Range Number R 14 E
---	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3 S 3 1/2 W OF PRATT, KS

2 WATER WELL OWNER: Wiloy Ash Sr. RR#, St. Address, Box # : R. R. 1 Box 114 City, State, ZIP Code : Rose Hill, Kansas 67133	Chinn #1 Chinn #1	Board of Agriculture, Division of Water Resources Application Number:
--	-----------------------------	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 130 ft. ELEVATION:
--	--

	Depth(s) Groundwater Encountered 1. 70 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 66 ft. below land surface measured on mo/day/yr 23 Feb, 82
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 100 gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 10 in. to 130 ft., and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	3 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded	

Blank casing diameter 5 in. to 110 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 2.14

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 6 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 110 ft. to 130 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 10 ft. to 130 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None	
Direction from well?	How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	15	Clay, brown with fine sand			
15	35	Sand, med to coarse and fine to med gravel			
35	70	Clay, dark brown and tan with white caliche			
70	105	Sand, fine to coarse and fine to med gravel			
105	135	Sand, med to coarse and fine to coarse gravel with very coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 23 Feb. 82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 11 Jun 82 under the business name of Central Well & Pump Inc. by (signature) Stanton

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

28

R

14

EW

SEC.

35

NE

1/4

NE

1/4

NW

1/4