

1 LOCATION OF WATER WELL:		Fraction Near Center NE 1/4 1/4		Section Number	Township Number	Range Number
County: Pratt				11	T 28 S	R 15 EW
Distance and direction from nearest town or city street address of well if located within city? 11/8 Mile West and 1/8 Mile South of Cullison, KS						
2 WATER WELL OWNER:		Stuart Briggeman				
RR#, St. Address, Box # :		Rural Route Cullison				
City, State, ZIP Code :		Pratt, KS 67124				
		Board of Agriculture, Division of Water Resources Application Number: 38,821				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION: unknown				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 91 ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm				
		Est. Yield 1500 gpm; Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 24 in. to 180 ft., and in. to ft.				
		WELL WATER TO BE USED AS:				
		5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No. <u>X</u>; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No <u>X</u>				
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped				
1 Steel 3 RMP (SR)		Welded <u>X</u>				
2 PVC 4 ABS		Threaded				
Blank casing diameter 16 in. to 128 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS:		From 128 ft. to 140 ft., From ft. to ft.				
		From 140 ft. to 160 ft., From ft. to ft.				
GRAVEL PACK INTERVALS:		From 20 ft. to 180 ft., From ft. to ft.				
		From ft. to ft., From ft. to ft.				
6 GROUT MATERIAL:		4 Other				
1 Neat cement 2 Cement grout 3 Bentonite						
Grout intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Known						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	71	Topsoil Clay Brownish Tan				
71	86	Sand & Gravel fine Med.				
86	97	Clay, Tan				
97	114	Sand & Gravel fine to med. Lime-stone 114'				
114	125	Clay white and Tan				
125	128	Streaks of Sandy Clay and streaks of gravel				
128	132	XXXXXXXXXXXXXXXXXXXX Gravel and Sand very fine, fine medium				
132	135	Gravel Med. to COarse				
135	172	Gravel fine to med clay streaks at 150' and 165'				
172	180	Sand Very fine with lots of clay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/22/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 3/31/89 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>						