


1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number			
County: Pratt		$\frac{1}{4}$ CSW $\frac{1}{4}$ NE $\frac{1}{4}$	18	T 28 S	R 15W E/W			
Distance and direction from nearest town or city? 5w 1s Cullison Ks.			Street address of well if located within city?					
2 WATER WELL OWNER: Red Tiger Drlg Co RR#, St. Address, Box #: 1720 Ks St Bldg City, State, ZIP Code: Wichita, Ks.			Board of Agriculture, Division of Water Resources Application Number: unknown					
3 DEPTH OF COMPLETED WELL: 185 ft. Bore Hole Diameter: 8 in. to 185 ft., and in. to ft.								
Well Water to be used as: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Observation well								
Well's static water level: 85 ft. below land surface measured on 2 month 23 day 79 year								
Pump Test Data: Well water was ft. after hours pumping gpm Est. Yield 65 gpm: Well water was ft. after hours pumping gpm								
4 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing dia: 145 in. to 145 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) Screen or Perforation Openings Are: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut Screen-Perforation Dia: 5 in. to ft., Dia in. to ft., Dia in. to ft. Screen-Perforated Intervals: From 145 ft. to 185 ft., From ft. to ft., From ft. to ft. Gravel Pack Intervals: From 10 ft. to 185 ft., From ft. to ft., From ft. to ft.								
5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well 3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below) 13 Watertight sewer lines Direction from well: SW How many feet 60 ? Water Well Disinfected? Yes No Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year: Pump Installed? Yes No If Yes: Pump Manufacturer's name Model No. HP Volts Depth of Pump Intake ft. Pumps Capacity rated at gal./min. Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other								
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 2 month 23 day 79 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on 2 month 27 day 80 year under the business name of Kellys Waterwell Serv. by (signature) <i>Kelly Price</i>								
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
		0	75	Top Soil-Clay				
		75	140	Sand-Clay				
		140	185	Sand-Gravel				
ELEVATION: unknown								
Depth(s) Groundwater Encountered 1. 85 ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)								
INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.								

OFFICE USE ONLY

T

28

R

15

END

SEC.

18

C 1/4 SW 1/4 NE 1/4