WIN		ER WELL:	/ WATE	R WELL RECORD F	orm WWC-5	KSA 82a-	1212 Township Number	Range Num	her
-	DN OF WA	DATT	5W 1/4	cil v. ACE	- 1/4		T 2 2 s	R 15	E
County: Distance a	nd direction	from nearest tow	n or city street a	ddress of well if located		17	1 7 3		
	LLISA			ESTSIDE					
		NER: D. R. LX	MINER OIL	CO.INC.		iz WINI	KLEPLECK, C	ULLISON, KS	
DD# C+ /	ddroes Bo	WEN. 17.77.27	RHOADINA	Y SUITE 40	1	1 . 41/11		re, Division of Water F	
		**	TAKS6	71/12				r: 782-19	
	ZIP Code		-1		151	# F! F\/AT		•	
AN "X"	IN SECTIO	N BOX:	Depth(s) Ground	water Encountered 1.	9	4 ft. 2.	ion:	t. 3	ft.
Ī I	!	[ace measured on mo/day	•	
_	- NW	- NE					er hours		
	1						er hours		
_₹ w ⊢		F	Bore Hole Diame	eter 7	1.50.		nd <i></i>	.in. to	ft.
₹ "	!	!!!	WELL WATER T	TO BE USED AS: 5	Public water	er supply 8	•	11 Injection well	ļ
ī _	_ SW		1 Domestic		Oil field wa		•	12 Other (Specify bel	ow)
l ľ	1	1 1	2 Irrigation				Observation well		, ,
l L	i	i	Was a chemical/l	bacteriological sample su	ibmitted to D	epartment? Yes	s; If	yes, mo/day/yr sample	was sub-
L _			mitted			Wate	er Well Disinfected? Yes	2.44.4	
TYPE C	F BLANK	CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOINTS: G	lued X.Y Clamped	·
1 Ste	eel	3 RMP (SR	ł)	6 Asbestos-Cement	9 Other	(specify below)	W	/elded	
2 PV		4_ABS		7 Fiberglass				hreaded	
Blank casi	ng diameter	 5	in. to	ft., Dia	in. to	<u></u>	ft., Dia	in. to	ft.
Casing hei	ght above la	and surface		.in., weight	2-65	lbs./ft	. Wall thickness or gaug	e No 71.4	
TYPE OF	SCREEN O	R PERFORATION	MATERIAL:		7 <u>PV</u>	<u>C</u>	10 Asbestos-c	ement	
1 Steel 3 Stainless steel 5 Fiberglass						8 RMP (SR) 11 Other (specify)			
2 Bra	ass	4 Galvanize	ed steel	6 Concrete tile	9 AB	S	12 None used	(open hole)	ĺ
SCREEN (OR PERFO	RATION OPENING	GS ARE: 🗸 🗸	5 Gauze	d wrapped		8 Saw cut	11 None (open h	nole)
1 Co	ntinuous slo	ot 3 Mil	Il slot ' 0	6 Wire w	rapped		9 Drilled holes		jo jo
2 Lo	uvered shut	ter 4 Ke	y punched	7 Torch	cut		10 Other (specify)		[
SCREEN-F	PERFORAT	ED INTERVALS:	From	<i>i.3.0</i> ft. to	150	ft., From		ft. to	ft.
			From	ft. to		ft., From		ft. to	ft.
G	RAVEL PA	CK INTERVALS:	From	1.2.0 ft. to	150	ft., From		ft. to	ft.
			From	ft. to		ft., From		ft. to	ft.
GROUT	MATERIAL	.: 1 Neat c	ement	2 Cement grout	3_Bento	onite 4 C	Other		
Grout Inter	vals: Fro	m <i>O</i>	ft. to /	ft., From	ft.	to	ft., From	ft. to	ft. (
What is the	e nearest so	ource of possible of	contamination:	INE		10 Livesto	ock pens 1	4 Abandoned water w	rell -
	ptic tank	4 Latera	, .	7 Pit privy		11 Fuel s	torage 1	5 Oil well/Gas well	1
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)			v) /
3 Wa	atertight sev	ver lines 6 Seepa	age pit	9 Feedyard		13 Insecti	cide storage		v) (
Direction f	rom well?					How many	y feet?		İ
FROM	ТО		LITHOLOGIC	LOG	FROM	ТО	LITHOL	OGIC LOG	
0	5	50/4							
5	40	CLAY							
40	90	SANP							
90	93	CLAY							
93	150	GRAVE	L)
									/
									,
									``
CONT	ACTORIO		P'S CERTIFICAT	ION: This water well	e (1) constru	oted (2) recor	setructed or (2) stragged	under my juriodiation	and wee
7 CONT	an (mar/di	UM LANDOWNEH	3.25	2	s (1) constru	and this recor	estructed, or (3) plugged d is true to the best of my	knowledge and helicit	Kanana
							n (mo/day/yr) 🛩 😘		
								m-	
under the	DUSINESS NO	typewriter or hall r	point pen PI EAC	ET WETL SETT	PRINT clear	by (signati	blanks, underline or circle	the correct answers	Send ton
							Section, Topeka, KS 666		
OWNER a	ind retain o	ne for your record	S.	,					