

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pratt	C ¼ NW ¼ NW ¼	30	T 28 S	R 15 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 ¾ south 5¼ west of Cullison					
2 WATER WELL OWNER: Mr. Smith Aldeberan Drilling		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: Pratt, Ks., Box 982		Application Number: T85-605			
City, State, ZIP Code: Pratt, Ks. 67124					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION:				
	Depth(s) Groundwater Encountered 1. 107 ft. 2. ft. 3. ft.				
	WELL'S STATIC WATER LEVEL 120 ft. below land surface measured on mo/day/yr . 7-3-85				
	Pump test data: Well water was ft. after hours pumping gpm				
	Est. Yield NA gpm; Well water was ft. after hours pumping gpm				
	Bore Hole Diameter..... 10 3/4 in. to ... 180 ft., and in. to ft.				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No. X.....; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes HTH No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X... Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded	
Blank casing diameter ... 5 in. to ... 160 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface..... 18 in., weight lbs./ft. Wall thickness or gauge No. ,258.....					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel		5 Fiberglass		7 PVC 10 Asbestos-cement	
2 Brass 4 Galvanized steel		6 Concrete tile		8 RMP (SR) 11 Other (specify)	
				9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot		5 Gauzed wrapped		8 Saw cut 11 None (open hole)	
2 Louvered shutter 4 Key punched		6 Wire wrapped		9 Drilled holes	
		7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From ... 160 ft. to ... 180 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ... 10 ft. to ... 180 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement					