WATER WELL RECORD		Form WV	VC-5	Division of Water	r Resources App. N	o.	
1 LOCATION OF WATER WELL:		Fraction		Section Number		Range Number	
County: Kiowa		1/4 NW 1/4 NW	1/4 SW 1/4	32	T 28 S	R 16 □E 🗹 W	
			Global Positioning System (GPS) information:				
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees)			
			Longitude: (in decimal degrees)				
Haviland 3 1/2 South			Elevation:				
				Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Dale Havse			Collection Method:				
RR#, Street Address, Box #:			GPS unit (Make/Model:)				
City, State, ZIP Code : Mullinville, KS				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
0.0, 0.000	le, NS		Est. Accuracy:				
3 LOCATE WELL							
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 158 ft.							
SECTION BOX: Det	oth(s) Ground	lwater Encountered (	water Encountered (1) ft. (2) ft. (3) ft.				
	Dump test date: Well water was the offer hours numping						
	gpm. Well water wasft. after hours pumping gpm						
NW NE	eter 9in. toft., andin. toft.						
W   E   Bore Hole Diameter 9							
Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
					Yes V No		
S If yes, mo/day/yr sample was submitted							
1 mile  Water well disinfected? ☑ Yes □ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Ø Glued Clamped Welded Threaded							
Casing diameter .5							
Casing diameter .v III. to							
Casing height above land surface. 24 in., Weight SDR.21 lbs./ft., Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)							
Steel Stainless	Steel	Z PVC	L)	Other (Specify)			
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From. 25 ft. to158 ft., From							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other							
Grout Intervals: From .3							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)							
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
Direction from well .East Distance from well30'							
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	IGGING INTERVALS	
0 12 Topsoil and	Brown Cla	v					
12 35 Brown Sand							
35 39 Tan Sandy							
39 120 Sand Fine t						***************************************	
120 125 Brown Clay							
125 158 Sand Fine t	to Medium						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .19-30-101 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/year) 5-25-10							
under the business name of .Tyler Water Well Service							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 426, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							