## WATER WELL RECORD Form WWC-5 KSA 82a-1212

						address of w					R 17	
2 1/2	N. 5 E. O	F GREENSBUR	R6, KS			. duuress ur W						
		R: s, Box # :			IG 167		Boar	rd of Agr.	icultur <b>e,</b> D	ivision o	of Water Resc	ources
City,	State, ZI	P code :	GREAT B	END, KS	67530-		Appl	lication	Nueber:			
3 LOCAT AN "X	E WELL'S L	OCATION WIT ON BOX:	.H	; 4 DE ; De	PTH OF COMPL pth(s) Groun	ETED WELL 1: dwater Encoun TER LEVEL	20 E tered	LEVATION 1.	: <b>55</b> ft.	2.	ft. 3.	ft
	; ;	¦ N	; (E	1 1 1	Pump t	estdata: Wel	l water »	185	ft. after	· ha	ours pumping	gp
H	! ! ! !	;	!!	!		gp <b>a:</b> We						gp
1	i	i	; ;	i		er <b>8.7</b> USED AS: <b>01</b>		120 f	t., and	in. to	ft.	
	: SW	¦ S	E!	i i								
. ,	; ;	i	i	; Was	a chemical/b	acteriologica	l sample Submitted	submitte 	d to depart	ment? No Water	; well disinfo	ected? <b>Ye</b> r
TYPE Blank Casin	DF BLANK Co casing dia g height a	ASING USED: ameter bove land s	02 PVC 5 i	n. to 1 12 in.,	CASIN OO ft., Dia weight	G JOINTS: GLU in. to lbs/ft	 ED ft	 : Dia	in. t	a f		********
TYPE Blank Casin TYPE SCREE	DF BLANK Co casing di g height a DF SCREEN O N OR PERFO	ASING USED: ameter bove land s OR PERFORAT RATION OPEN	02 PVC 5 i Surface TON MATE	n. to 1 12 in., RIAL: 07 : 08	CASIN 00 ft., Dia weight PVC SAN CUT	G JOINTS: GLU in. to lbs/ft	ED ft . Wall (	., Dia thickness	in. t or gauge N	 o f o <b>. 26</b>		
TYPE Blank Casin TYPE SCREE	DF BLANK Co casing di g height a DF SCREEN O N OR PERFO	ASING USED: ameter bove land s OR PERFORAT RATION OPEN	02 PVC 5 i Surface TON MATE	n. to 1 12 in., RIAL: 07 : 08 From	CASIN OO ft., Dia weight PVC SAN CUT	6 JOINTS: GLU in. to lbs/ft 120 ft., Fi	ft. Wall (	., Dia thickness ft. to	in. t or gauge N	 o f o <b>. 26</b>		
TYPE Blank Casin TYPE SCREE	OF BLANK Co casing dia g height a OF SCREEN O N OR PERFOR	ASING USED: ameter bove land s OR PERFORAT RATION OPEN	02 PVC 5 i surface ION MATE IINGS ARE	n. to 1 12 in., RIAL: 07 : 08 From From From	CASIN 00 ft., Dia weight PVC SAW CUT  100 ft. to ft. to 25 ft. to	9 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F	ft. Wall (	thickness  ft. to ft. to ft. to	in, to or gauge N	 o f o <b>. 26</b>		
5 TYPE Blank Casin TYPE SCREE SCREE	OF BLANK Co casing dia g height a OF SCREEN on N OR PERFORM N PERFORAT! GRAVEL PAI MATERIAL Intervals	ASING USED: ameter bove land s OR PERFORAT RATION OPEN ED INTERVAL  CK INTERVAL  03 BENTO : From	O2 PVC 5 isurface ION MATE IINGS ARE S: S: MITE ft. t	n. to 1 12 in., RIAL: 07 : 08  From From From From	CASIN OO ft., Dia weight PVC SAN CUT  100 ft. to ft. to 25 ft. to ft. to	6 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F 120 ft., F ft., F	ft.	ft. to ft. to ft. to	in, to or gauge N	 o f o <b>. 26</b>	t.	
5 TYPE Blank Casin TYPE SCREE SCREE	OF BLANK Co casing dia g height a OF SCREEN on N OR PERFORM N PERFORAT! GRAVEL PAI MATERIAL Intervals	ASING USED: ameter bove land s OR PERFORAT RATION OPEN ED INTERVAL  OS BENTO : From rest source	O2 PVC 5 isurface ION MATE IINGS ARE S: S: MITE ft. t	n. to 1 12 in., RIAL: 07 : 08  From From From From	CASIN OO ft., Dia weight PVC SAN CUT  100 ft. to ft. to 25 ft. to ft. to	9 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F 120 ft., F	ft.	ft. to ft. to ft. to	in. tor gauge N	o f	t.	
5 TYPE Blank Casin TYPE SCREE SCREE	OF BLANK Cocasing diagrams of Screen	ASING USED: ameter bove land s OR PERFORAT RATION OPEN ED INTERVAL  CK INTERVAL  03 BENTO: From rest source well? NW	O2 PVC 5 isurface ION MATE HINGS ARE S:	n. to 1 12 in., RIAL: 07 : 08  From From From From	CASIN 00 ft., Dia weight PVC SAN CUT  100 ft. to ft. to 25 ft. to ft. to	6 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F 120 ft., F ft., F	ft.	ft. to ft. to ft. to	in. to or gauge N  ft. ft. ft. ft. ft.	o f lo. <b>26</b>	t.	
5 TYPE Blank Casin TYPE SCREE SCREE 6 GROUT Grout What Direc FROM	OF BLANK Cocasing diagrams of the common of	ASING USED: ameter bove land s OR PERFORAT RATION OPEN ED INTERVAL  O3 BENTO: From rest source well? NM  SILT 4 GREY C TAN CL	O2 PVC 5 i Surface TION MATE HINGS ARE S: S: MITE ft. t c of poss	n. to 1 12 in., RIAL: 07 : 08  From From From From LITHOLOG	CASIN 00 ft., Dia weight PVC SAN CUT  100 ft. to ft. to 25 ft. to ft. to	6 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F 120 ft., F ft., F	ft.,	ft. to ft. to ft. to	in. to or gauge N  ft. ft. ft. ft. ft.	o f lo. <b>26</b>	t. How many fe	
5 TYPE Blank Casin TYPE SCREE SCREE 6 GROUT Grout What Direc FROM 5	OF BLANK Cocasing diagrams of the common of	ASING USED: ameter bove land s OR PERFORAT RATION OPEN ED INTERVAL  O3 BENTO: From rest source well? NM  SILT 4 GREY C TAN CL	O2 PVC 5 i Surface TION MATE HINGS ARE S: S: MITE ft. t c of poss	n. to 1 12 in., RIAL: 07 : 08  From From From From LITHOLOG	CASIN 00 ft., Dia weight PVC SAN CUT  100 ft. to ft. to 25 ft. to ft. to	6 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F 120 ft., F ft., F	ft.,	ft. to ft. to ft. to	in. to or gauge N  ft. ft. ft. ft. ft.	o f lo. <b>26</b>	t. How many fe	
TYPE Blank Casin TYPE SCREE SCREE GROUT Grout What Direc FROM	OF BLANK Cocasing diagrams of the common of	ASING USED: ameter bove land s OR PERFORAT RATION OPEN ED INTERVAL  O3 BENTO: From rest source well? NM  SILT 4 GREY C TAN CL	O2 PVC 5 i Surface TION MATE HINGS ARE S: S: MITE ft. t c of poss	n. to 1 12 in., RIAL: 07 : 08  From From From From LITHOLOG	CASIN 00 ft., Dia weight PVC SAN CUT  100 ft. to ft. to 25 ft. to ft. to	6 JOINTS: 6LU in. to lbs/ft 120 ft., F ft., F 120 ft., F ft., F	ft.,	ft. to ft. to ft. to	in. to or gauge N  ft. ft. ft. ft. ft.	o f lo. <b>26</b>	t. How many fe	

This Water Well Record was completed on Jan/day/yrp 08/19/92

Water Well Contractor's License No. 224 This under the business name of CARL HAYSE WATER WELL SVC