WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section | number | Township number | Range number |] | |
|---|------------|------------------|------------------|---------|--------|--|---|---|--|
| 1. Location of well: | Kiowa | NW 1/4 SE 1/4 NW | J _{1/4} | 2 | .2_ | 1 28 s | R /TW EN | | |
| 2. Distance and direction from nearest town or city: $4\omega + 15\sigma = 3$. Owner of well: | | | | | | Lton Ross | | | |
| Street address of well location if in city: HAVILAND, K5 R.R. or street City, state, z | | | | | | reet: re, zip code: Haviland, Kansas | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia. 30 in. Completion date ———————————————————————————————————— | | 1 | |
| X well | | | | | | 7Cable toolRotaryDrivenDugHollow rodJettedBoredXReverse rotary 8. Use:DomesticPublic supplyIndustryXIrrigationAir conditioningStockLawnOil field waterOther | | | |
| | | | | | | | | | |
| S DRAINING | | | | | | 9. Casing: Material STA Height Above or below Threaded Welded Surface 1 2 in. RMP PVC Weight 32.7 lbs./ft. | | | |
| 1 M | lile ———I | L' . | | E | T - | Dia 6 in. to 6 ft. dep | th Wall Thickness: inches or | | |
| 5. Type and colar of | t material | | | From | То | 10. Screen: Manufacturer's n | ame | .] | |
| Sandy soil | | | | 0 | 2 | Type TES FLOO | Dia. 16" | <u>.</u> | |
| Clay, tan and sandy | | | | 2 | 50 | Slot/gauze <u>Y8</u> Set between <u>/40</u> | ft. and <u>180</u> ft | : | |
| Sand, fine and silty | | | | 50 | 60 | Grovel pack? Size ra | ndft | <u>-</u> | |
| Sand, fine and tan clay mixed | | | | 60 | 82 | 11. Static water level: | mo./day/yr face Date 15 Aug 79 | | |
| Sand, fine to coarse and coarse gravel | | | | 82 | 108 | 12. Pumping level below land | · · · · · · · · · · · · · · · · · · · | | |
| Clay, tan and gray with sand and gravel | | | | 108 | 120 | 123 ft. after b | nrs. pumping/200 g.p.m. | | |
| Sand, fine to coarse and medium gravel | | | | 120 | 150 | 13. Water sample submitted: | mo./day/yr | 7 | |
| XXX Sand, fine to coarse and coarse gravel | | | | 150 | 180 | 14. Well head completion: | Date | 4 | |
| Clay, tan and sandy | | | | 180 | 184 | Pitless adapter 15. Well grouted? | Inches above grade | ┦ " | |
| Clay, yellow | | | | 184 | 190 | | Bentonite Concrete | 17. | |
| Shale, black | | | | 190 | 200 | 16. Nearest source of possible | contamination: NONE | | |
| + : | | | | | | Well disinfected upon comple | tion?_X_YesN | <u>,</u> } | |
| | | | | | | 4 . 1 | Not installed WMのおち | . | |
| | | | | | | Model number 2M 13 Length of drop pipe 160 | HP Volts _ ft. capacity /2<i>00</i>g.p.m. | . (§ | |
| | | | | | | Type: Submersible | X Turbine | " | |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | Reciprocating Other |] ^{&} [) | |
| 18. Elevation: 19. Remarks: 8 x 23 x 8 Slab-poured Topography: Hill Slope Topography: Slope | | | | | | 20. Water well contractor's of This well was drilled under m is true to the best of my know | y jurisdiction and this report ledge and belief. |] | |
| Upland | | | | | | Central Well & Business name Address Pao Box 10 Signed | License No. 32 Pratt Kansas | 1/4 1/4 1/4 1/4 1/4 1/4 1/4 1/4 1/4 1/4 | |
| ∨alley | | | | | | Authorized rep | resentative — 70 | コッド | |