

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Kiowa		SW ¼ NE ¼ SW ¼		16		T 28 S		R 18 W EW	
Distance and direction from nearest town or city street address of well if located within city? 419 W. Kansas Avenue, Greensburg, Kansas 67054									
2 WATER WELL OWNER: Coastal Mart #2509									
RR#, St. Address, Box # : 419 W. Kansas					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Greensburg, Kansas 67054					Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 99.5 ft. ELEVATION: 0						
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL: 87.64 ft. below land surface measured on mo/day/yr 11/14/02						
			Pump test data: Well water was NA ft. after hours pumping gpm						
			Est. Yield NA gpm: Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 12 in. to 100 ft. and in. to ft.						
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
			Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted						
			Water Well Disinfected? Yes No ☒						
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded ☒									
Blank casing diameter 4 in. to 69.5 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 69.5 ft. to 99.5 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 66 ft. to 100 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 63 ft. From 63 ft. to 66 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? W How many feet? 50									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 0.5 Asphalt									
0.5 2 Clay, Dark Brown									
2 16 Silty Clay, Light Brown									
16 38 Silty Clay, Light Brown with Light Gray Mott									
38 49 Silty Sand, Light Brown									
49 51 Clayey Silt, Light Brown									
51 61 Silty Sand, Light Brown									
61 65 Clay, Mottled Light Brown, Light Gray									
65 100 Sand, Light Brown and Light Red Brown									
B-1 Flushmount									
Project Name: Handex - Greensburg									
GeoCore # 1037									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/14/02 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/12/02									
under the business name of GeoCore Inc. by (signature) <i>Joe Bell</i>									