


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 10 Township Number T 28 S Range Number R 18 E
 County: Kiowa

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Volz Oil Company Volz
 RR#, St. Address, Box # : Norman Volz
1000 E Kansas
 City, State, ZIP Code : Greensburg, KS 67054
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 89 ft. ELEVATION: 2226.77
 Depth(s) Groundwater Encountered 1 76 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 75.45 ft. below land surface measured on mo/day/yr. 05/18/04 & 05/19/04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Vapor Obstruction
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No (No)

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X
 Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface -4.8 in., weight lbs./ft. Wall thickness or gauge No. sch 40 AIC
 TYPE OF SCREEN OR PERFORATION MATERIAL: 3 PVC
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 59 ft. to 89 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 57 ft. to 89 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 1 ft. to 57 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
LUST SITE
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Concrete			
1	10	Sand Fill			
10	21	Clay, silty			
21	40	Clay, very fine, sandy			
40	44	Sand, clayey, very fine to fine			
44	53	Clay, silty			
53	64	Sand, fine to medium, clayey			
64	80	Sand, moist, fine to coarse			
80	89	Sand & gravel, rounded up to 1"			VOBW @ (0)

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/29/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 594 This Water Well Record was completed on (mo/day/yr) 7/12/04 under the business name of Coronado Great Plains, Inc by (signature) [Signature]