


1 LOCATION OF WATER WELL: Fraction ~~SE~~ $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$ Section Number 16 Township Number T 28 S Range Number R 18 EW

Distance and direction from nearest town or city street address of well if located within city?
 222 E. Kansas, Greensburg, KS 67054

2 WATER WELL OWNER: Volz Oil Company
 RR#, St. Address, Box # : Norman Volz
 City, State, ZIP Code : 1000 E. Kansas Greensburg, KS 67054
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 89 ft. ELEVATION: 222.7
 Depth(s) Groundwater Encountered 1 ~77.55 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL NM ft. below land surface measured on mo/day/yr NM
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 2 in. to 89 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface NM in., weight lbs./ft. Wall thickness or gauge No. Sch 40 PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 59 ft. to 89 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 57 ft. to 90 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 1 ft. to 57 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Lust Site
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete	55	65	Sand, medium to gravel
0.5	9	Silt	65	67	Sand with gravel, medium to gravel
9	18	Sand, very fine grained	67	76.5	Sand with gravel, fine to some gravel
18	22	Sandy silt, very fine grained	76.5	77	Clay, wet
22	23	Silt, very fine grained	77	79	Sand with gravel, fine with some gravel
23	23.5	Sand, fine grained	79	90	Gravel, medium to pebbles
23.5	24	Clay			
24	37	Sand, very fine grained			
37	38	Silty clay			
38	38.5	Sand, fine grained			
38.5	39	Silty clay			
39	44	Sand, fine grained			
44	53	Clayey sand, fine grained			
53	55	Sand, fine to medium grained			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/02/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 594 This Water Well Record was completed on (mo/day/yr) 6/16/05 under the business name of Coranco Great Plains, Inc. by (signature) Meghan E. Kelly