

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Kiowa		SW ¼ NW ¼ SE ¼	16	T 28 S	R 18 E W
Distance and direction from nearest town or city street address of well if located within city? 95'N & 90'W of NW corner of Kansas & Sycamore					
2 WATER WELL OWNER: Koehn 66					
RR#, St. Address, Box # : 13605 W. Maple, Suite 101			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS 67235			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 98.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 76.55 ft. below land surface measured on mo/day/yr 11/20/2007			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 10.5 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No ☒ ; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter 4 in. to 73.5 ft. Dia		7 Fiberglass		8 Concrete tile	
Casing height above land surface 0 in., weight		8 RMP (SR)		9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL		7 PVC		10 Asbestos-cement	
1 Steel		3 Stainless steel		11 Other (specify)	
2 Brass		4 Galvanized steel		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		3 Mill slot		9 Drilled holes	
2 Louvered shutter		4 Key punched		10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		7 Torch cut		11 None (open hole)	
From 73.5 ft. to 98.5 ft.		8 Wire wrapped		From ft. to ft.	
GRAVEL PACK INTERVALS:		9 ABS		From ft. to ft.	
From 70 ft. to 98.5 ft.		10 Other (specify)		From ft. to ft.	
FROM ft. to ft.		11 None (open hole)		From ft. to ft.	
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From 0 ft. to 2 ft.		From 2 ft. to 70 ft.		From 70 ft. to ft.	
What is the nearest source of possible contamination:		7 Pit privy		10 Livestock pens	
1 Septic tank		4 Lateral lines		11 Fuel storage	
2 Sewer lines		5 Cess pool		12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		13 Insecticide storage	
Direction from well?		9 Feedyard		14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
				How many feet?	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	5	Clay, Brown			
5	20	Clay, silty, sandy (f), Brown			
20	37	Clay, v. silty, sandy (f), Brown			
37	39	Sand,			
39	43	Silt, clayey, sandy, soft, Brown			
43	52	Clay, v. hard, silty, sandy, Brown			
52	55	Clay, firm, silty, Brown			
55	60	Sand (f-m),			
60	76	Sand (f-c),			
76	79	Sand (f-m),			
79	105	Sand (f-c), gravel (sm. to med.),			
MW43, Tag # 0041125, Flushmount					
Project Name: GF - Koehn 66					
GeoCore # 1290, KDHE # U1 049 13273					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/8/2007 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/12/07					
under the business name of GeoCore, Inc. by (signature) <i>Don Koehn</i>					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4