

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Pottawatomie Fraction SE 1/4 NW 1/4 SE 1/4 Section Number 30 Township Number T 9 S Range Number R 10 EW

Distance and direction from nearest town or city street address of well if located within city? 1/2 N 1/4 W OF Wamego Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: N 39.235042 Longitude: W 96.337244

2 WATER WELL OWNER: Robert Riatt RR#, St. Address, Box #: 16201 Elm Slough rd City, State, ZIP Code: Wamego, KS 66547 Elevation: 955 Datum: Data Collection Method: Hand Held

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram] 4 DEPTH OF COMPLETED WELL: 65 ft. Depth(s) Groundwater Encountered (1) 22 ft. (2) 54 ft. (3) 58 ft. WELL'S STATIC WATER LEVEL: 22 ft. below land surface measured on mo/day/yr. 4-22-09 Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield: 20 gpm Well water was ... ft. after ... hours pumping ... gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

5 TYPE OF CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought Iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded Blank casing diameter 5 in. to 60 ft., Diameter in. to ... ft., Diameter in. to ... ft. Casing height above land surface 24 in., Weight ... lbs./ft. Wall thickness or gauge No. SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RM (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw Cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 60 ft. to 65 ft. GRAVEL PACK INTERVALS: From 24 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 24 ft., From ... ft. to ... ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer Storage 13 Insecticide Storage 14 Abandoned water well 15 Oil well/gas well 16 Other (specify below) Existing well Direction from well? N.W. How many feet? 40'

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-2 Topsoil, 2-5 brown silty clay, 5-11 very fine brown sand, 11-17 Tan silty clay, 17-42 very fine brown sand, 42-54 Tan silty clay, 54-58 Fine to coarse brown sand, 58-72 brown chert, 72-80 Grey limestone

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-22-09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/year) 5-6-09 under the business name of Stroder Drilling Co, Inc by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.