


1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 SE 1/4 Section Number 16 Township Number T 28 S Range Number R 18 E
 County: KIOWA

Distance and direction from nearest town or city street address of well if located within city?
99' 2" West of Oak St 18' 8" North of US 54 Hwy

2 WATER WELL OWNER: FARMERS GRAIN & SUPPLY
 RR#, St. Address, Box #: 102 E KANSAS Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Greensburg, KS Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 90.5 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 70.0 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 28.62 ft. below land surface measured on mo/day/yr 1/8/94
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 7 5/8 in. to 90.5 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well M.W.S.
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 2 in. to 65.5 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface: 7 in., weight lbs./ft. Wall thickness or gauge No. Sched 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 65.5 ft. to 90.5 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 62.3 ft. to 91.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 1.0 ft. to 56.9 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	2'	TOP SOIL, DK BROWN			
2'	14'	CLAY, DK BROWN			
14'	18'	CLAY, TAN, SANDY Very Fine - Fine grained			
18'	23'	CLAY, DK BROWN			
23'	25'	SILT, TAN, SANDY			
25'	30'	CLAY, BROWN, SILTY			
30'	39'	SILT, TAN, CLAY, Very Fine SAND			
39'	50'	SILT, TAN, SANDY, Very Fine - Fine grained			
50'	60'	Clay, Brown, sandy Fine, Caliche			
60'	70'	SANDY, Brown, Fine grained, Clayey			
70'	91.5'	SANDY, Brown, Fine to coarse, w/ pebbles to 2" dia, rounded			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/8/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 463 This Water Well Record was completed on (mo/day/yr) 4/28/94 under the business name of TEST by (signature) Way P. [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4