

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Kiowa	Fraction SW 1/4 1/4 1/4	Section number 13	Township number T 28 S R 19	Range number 19
2. Distance and direction from nearest town or city: 3 Mi. W. of Greensburg; 1/4 Mi. N. of 54 Hwy.				3. Owner of well: Mark Dirks R.R. or street: Greensburg, Kansas City, state, zip code:		
4. Locate with "X" in section below:		Sketch map: Well No. 1 (TH 1-76)			6. Bore hole dia. 30 in. Completion date 1-26-77 Well depth 200 ft.	
		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
		9. Casing: Material Stl. Height: Above amboten Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 31.75 lbs./ft. Dia. 16 in. to 153 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 188			10. Screen: Manufacturer's name Doerr Metal Products Type Stl. Dia. 16" Slot/gauze 1/8 Length 48' Set between 126 ft. and 154 ft. 180 ft. and 200 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/8x3/8	
5. Type and color of material		From	To	11. Static water level: <input type="checkbox"/> mo./day/yr. 61 ft. below land surface Date 1-26-77		
Soil		0	2	12. Pumping level below land surfaces: 97 ft. after 4 hrs. pumping 800 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 1500 g.p.m.		
Brown clay		2	43	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
Fine sand		43	68	14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade		
Med. to coarse sand & gravel		68	155	15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
Brown & gray clay		155	170	16. Nearest source of possible contamination: ft. 3500 Direction East Type Farm Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Brown clay w/sand & gravel		170	200	17. Pump: Not installed Manufacturer's name Layne & Bowler Model number 12RL HP 80 Volts <input type="checkbox"/> Length of drop pipe 120 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
Blue shale		200		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name License No. Address Wichita, Kansas Signed [Signature] Date 1-27-77 Authorized representative		
18. Elevation:		(Use a second sheet if needed)		19. Remarks:		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						

T 28
 R 19
 S 13
 Sec 13
 1/4 SW 1/4

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5