

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction: <u>SW ¼ NW ¼ NE ¼</u>	Section Number: <u>22</u>	Township Number: <u>28 N</u>	Range Number: <u>2 E/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>See below</u>					
2 WATER WELL OWNER: <u>Pot McClure</u> RR#, St. Address, Box # : <u>5411 W. 4th St.</u> City, State, ZIP Code : <u>Clearwater, KS 67026</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>63</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>4</u> ft. below land surface measured on mo/day/yr <u>5-9-97</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>20</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>11</u> in. to <u>63</u> in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well <u>1 Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes..... No.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) <u>2 PVC</u> 4 ABS Blank casing diameter <u>5</u> in. Dia. <u>43</u> in. to ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No.		CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From <u>43</u> ft. to <u>63</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>4</u> ft. to <u>63</u> ft., From ft. to ft.		7 PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) 8 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
6 GROUT MATERIAL: 3 Neat cement 4 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>4</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: <u>1 Septic tank</u> 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>Southeast</u> How many feet? <u>150 ft.</u>					
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS		
0	2	top soil			
2	8	clay			
8	12	fine sand			
12	36	clay			
36	47	fine to medium sand			
47	63	shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-9-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>5-9-97</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Thelma Becker</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					