KSA 82a-1212 WATER WELL RECORD Form WWC-5 RANGE NUMBER LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER NW28 R 2W Sedgwick NE 1/4 12 т s 1/4 Distance and direction from nearest town or city street address of well if located within city? 119th N. & 34th S. & 3/8th mile West on Fire Fly Wichita, Kansas LIFESTYLE HOMES WATER WELL OWNER: Board of Agriculture, Division of Water Resource 1354 S. Ridge Road RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: Application Number: ZIP CODE 4 DEPTH OF COMPLETED WELL: 116 ELEVATION: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft ft. Depth of groundwater Encountered: 35 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW NE-Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Φ 12 to 116 ₹ Bore Hole Diameter and in. ft. in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO Was Water Well Disinfected? (YES) submitted TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter to 75 Dia. to Dia in. ft. 12 2.35 Casing height above land surface: in . Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3 Stainless Steel 5 Fiberglass 1. Steel 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 8. Saw cut 2. Louvered shutter 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 75 116 ft.. From From ft. ft. to ft. From From ft. ft. 24 ft. GRAVEL PACK INTERVALS: 116 From ft.. From ft tο ft. From ft. to ft.. From ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: 24 From ft., From ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Yet 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? LITHOLOGIC LOG LITHOLOGIC LOG From To From Τо topsoil **70** clav 70 medium sand 80 clav 80 98 medium sand 98 116 gray and red shale

Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3. under my jurisdiction and 3/21/2014 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year)

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

3/24/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb