WATER WELL RECORD		Form W	VC-5	Division of Water Resources App. No.				
1 LOCATION OF WATER WELL:		Fraction	,	Section Number				
County: Sedawick			1/4 SW 1/4 SE 1/4 NW 1/4			T 28 S		
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:								
from nearest town or intersection: If at owner's address, check here . Latitude:								
-	•					Longitude: (in decimal degrees)		
Elevation:								
2 WATER WELL OWNER: Jeff Parsons					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
					Collection Method: GPS unit (Make/Model:)			
RR#, Street Address, Box #: 2765 Saratoga City, State, ZIP Code : Goddard, KS 67052					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City	, State, 2	Goddard Goddard	3, KS 67052					
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 100 ft.								
	SECTION BOX: Depth(s) Groundwater Encountered (1).50 ft. (2)							
1	SECTION BOX: Depth(s) Groundwater Encountered (1).50 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL.50 ft. below land surface measured on mo/day/yr							
Pump test data: Well water wasft. after hours pumping								
EST. YIELD.18gpm. Well water wasft. after								
1 1	W E Bore Hole Diameter 19in. toft., andin. toft.							
WEDD WITTER TO DE COED IIS. I done water supply Geodaleina I injection wen								
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Industrial ☑ Domestic-lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department?								
S If yes, mo/day/yr sample was submitted								
	1 mile	Water well disin	fected? 📝 Yes 🔲 1	No				
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5								
Casing height above land surface12								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel • ☑ PVC ☐ Other (Specify)								
Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify)								
From								
GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From ft. to ft.								
From								
CONTIT MATERIAL. Next coment Coment group D Dantonita College								
GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
	Sewer li			Fuel storage	Abandoned	water well	,	
	Watertig	ht sewer lines Seepage p	it Feedyard	Fertilizer st				
		n well Northwest						
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	GGING INTERVALS	
0	5	Topsoil •						
5	20	White Clay						
20	50	Gray Shale						
50	52	Hard∕Void					•	
52	80	Gray/Red Shale						
80	85	Red Shale (very hard)			,			
85	100	Gray Shale						
-		•						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .8/21/2015 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 238 This Water Well Record was completed on (mo/day/year) 8/24/2015								
under the business name of Premier Pump & Well Service, Inc. by (signature) by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to								
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								