WATER WELL R		WWC-5		ision of Water				
Original Record		ge in Well Use		urces App. No.		Well ID		
1 LOCATION OF WA		Fraction NW1/4 SW1/4 NW1/4	1	tion Number 3	Township Number	er Range Numbe R 2 □ E ■		
2 WELL OWNER: La					(if unknown, distance and			
Business: direction from nearest town or intersection): If at owner's address, check here:								
Address: 2530 S 16	7TH ST W							
City: GODDARD State: KS ZIP: 67052								
3 LOCATE WELL		MPLETED WELL:	60 n	5 Latitud	۵٠	(desimal des	roac)	
WITH "X" IN	Depth(s) Groundwater	2 ft.	Longitude:					
SECTION BOX:	2) ft. 3) ft., or 4)			Horizontal Datum: □ WGS 84 □ NAD 83 □ NAD 27				
<u> </u>	0ft.	Source for Latitude/Longitude:						
	below land surface, measured on (mo-day-y above land surface, measured on (mo-day-y)	
NW NE	Pump test data: Well water was ft.				(WAAS enabled? ☐ d Survey ☐ Topogra			
W E	after hours pumping gpm			Online Mapper:				
SW SE	I .	water was fi						
	after hours pumping			6 Elevation:ft. Ground Level TOC				
S	Bore Hole Diameter: 10.5 in. to 60 ft.			Source:				
	1 mile in. to							
7 WELL WATER TO		C		10 🗖 0:17	"-1137-A D A 1-			
1. Domestic:		ater Supply: well ID ng: how many wells?				ase	••••	
Lawn & Garden	7. Aquifer Recharge: well ID			11. Test Hole: well ID				
☐ Livestock	8. Monitoring: well ID			12. Geothermal: how many bores?				
2. Irrigation					a) Closed Loop			
3. ☐ Feedlot 4. ☐ Industrial	☐ Air Sparg ☐ Recovery		extraction					
4. ☐ Industrial ☐ Recovery ☐ Injection 13. ☐ Other (specify):								
Water well disinfected? ■ Yes □ No								
8 TYPE OF CASING USED: ☐ Steet ■ PVC ☐ Other CASING JOINTS: ■ Glued ☐ Clamped ☐ Welded ☐ Threaded								
Casing diameter 5 in to 60 ft., Diameter in to ft., Diameter in to ft. Diameter in to ft. Casing height above land surface 12 in Weight lbs/ft. Wall thickness or gauge No. SDR-26								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot								
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. to ft. to								
GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From ft. to ft., From ft. to ft.								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other.								
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ■ Bentonite ☐ Other								
Nearest source of possible contamination:								
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage ☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well								
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well								
Other (Specify) NONE Direction from well?								
Direction from well?	LITHOLO		FROM			PLUGGING INTERVA	AT S	
	OP SOIL	aic roa	FROM	10 LI	THO. LOG (CONI.) OF	FLUGGING INTERVA	ALS	
	LAY							
	ED SAND				***** **** WITH TAX *** *** ***	*** · · · · · · · · · · · · · · · · · ·		
24 60 SI	HALE							
			NT-4-					
			Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) 01/03/2017 and this record is true to the last of my knowledge and belief								
Kansas Water Well Contractor's License No. 884 This Water Well Record was completed on (200-dy-year) 01/10/2017 under the business name of WENINGER DRILLING. LLC.								
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015								