## WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NWSE NW8 28 R **2W** 1/4 1/4 1/4 Т S E/W Distance and direction from nearest town or city street address of well if located within city? 2611 S. Saratoga Circle Wichita, Kansas MARGREITER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 8973 S.E. 96th ZIP CODE: 67226 Valley Center, Kansas CITY, STATE: Application Number: 4 DEPTH OF COMPLETED WELL: 116 FI EVATION LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/31/17 Pump test data: Well water was ft. after hours of pumping @ NW NF. apm Est. Yield: Well water was hours of pumping @ apm ft. after gpm ≌ Bore Hole Diameter 12 to 116 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 7. Lawn and garden only SE 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) YES Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS 5 Blank casing diameter 34 ft., Dia. ft., Dia. in. to ft 12 Weight: 2.35 Casing height above land surface: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 7. Torch cut 9. Drilled holes 5. Gauzed wrapped 11. None (open hole) 8. Saw cut 2. Louvered shutter 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 34 116 From to ft., From ft. ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: 24 116 to From ft., From ft. ft. From ft. to From ft. to ft. GROUT MATERIALS: Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite 4 Grout Intervals: From ft 24 ft., ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 5. Cess Pool 14. Abandon water well 2. Sewer lines None Yet 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? LITHOLOGIC LOG From To From Τo LITHOLOGIC LOG 3 0 topsoil 3 18 clav 18 24 very fine sand 24 116 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and

Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/31/2017 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/3/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp