WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 Sedgwick SE 1/4 1/4 8 Т 28 S R 2W E/W Distance and direction from nearest town or city street address of well if located within city? 2611 S. Saratoga Circle Wichita, Kansas STOVALL CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource 11110 E 26th N. Ste.#200 RR#,ST. ADDRESS,BOX #: ZIP CODE: 67226 Wichita, Kansas CITY, STATE: Application Number: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 116 ELEVATION: WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft. ft WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/31/17 Pump test data: Well water was ft. after ΝE gpm Est. Yield: apm Well water was ft. after hours of pumping @ Φ apm ≅∾ Bore Hole Diameter 12 to 116 and in ft. WELL WATER TO BE USED AS: 11. Injection well Dewatering SW SE 3. Feedlot 5. Public water supply 7. Lawn and garden only 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 5 CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 Blank casing diameter in. to 34 ft.. Dia. in. to ft.. Dia in. ft. to 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steet 5. Fiberglass 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 6. Concrete Tile 12. None used (open hole) 2. Brass Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 34 From to 116 ft. From to ft. From to ft.. From ft. 24 GRAVEL PACK INTERVALS: ft. to 116 From ft., From ft. to ft. From ft to ft.. From to ft. **GROUT MATERIALS:** 6 1. Neat cement 2 Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft 24 ft From ft. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Yet 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? How many feet? From Τо LITHOLOGIC LOG From То LITHOLOGIC LOG 0 3 topsoil 3 18 clay 18 24 very fine sand 24 116 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 10/31/2017 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb