

KSA 82a-1212

1 LOCATION OF WATER WELL: County: Sedgwick NW 1/4 SW 1/4 NW 1/4 Section Number 4 Township Number 28 Range Number 2 EW Distance and direction from nearest town or city street address of well if located within city? 12650 S 183rd Goddard KS.

2 WATER WELL OWNER: Tony Strunk. RR#, St. Address, Box #: 18112 W Paymore City, State, ZIP Code: Goddard KS 67052 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW corner]

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 20 ft. below land surface measured on 9-30-85. WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on 9-30-85. Pump test data: Well water was 20 ft. after 20 hours pumping 20 gpm. Est. Yield 20 gpm: Well water was 20 ft. after 20 hours pumping 20 gpm. Bore Hole Diameter 11 in. to 50 ft., and 50 in. to 50 ft. WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below). Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No.

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). Blank casing diameter 5 in. to 20 ft., Dia 20 in. to 20 ft., Dia 20 in. to 20 ft., Dia 20 in. to 20 ft. Casing height above land surface 1.2 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 26. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Mill slot, 3 Key punched, 4 Gauzed wrapped, 5 Wire wrapped, 6 Torch cut, 7 Saw cut, 8 None (open hole). SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From 20 ft. to 40 ft., From 20 ft. to 40 ft., From 20 ft. to 40 ft. GRAVEL PACK INTERVALS: From 13 ft. to 40 ft., From 13 ft. to 40 ft., From 13 ft. to 40 ft., From 13 ft. to 40 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout intervals: From 3 ft. to 13 ft., From 13 ft. to 40 ft., From 13 ft. to 40 ft., From 13 ft. to 40 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? East. How many feet? 150.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1318 This Water Well Record was completed on (mo/day/yr) 9-30-85 under the business name of Weninger Drilling by (signature) Weninger.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500. Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.