

1) LOCATION OF WATER WELL:

Fraction	Township Number	Range Number
SW ¼ NW ¼ SW ¼	T 28 S	R 2 E

County: Sedg
Distance and direction from nearest town or city street address of well if located within city?
West 174 South Goddard KS.

2) WATER WELL OWNER:
RR# , St. Address, Box # :
City, State, ZIP Code :

Pat Mosley
RR Goddard KS 67052

Board of Agriculture, Division of Water Resources
Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4) DEPTH OF COMPLETED WELL: 6.2 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 2.8 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL ... 2.8 ft. below land surface measured on mo/day/yr 3-31-86
Pump test data: Well water was 30 ft. after hours pumping 20 gpm
Est. Yield 30 gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter .11 in. to 6.2 ft., and in. to ft.
WELL WATER TO BE USED AS:
☒ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)
☐ Irrigation ☐ Industrial ☐ Lawn and garden only ☐ Observation well
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5) TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass	Threaded.	

Blank casing diameter .5 in. to 30 ft., Dia. in. to ft., Dia. in. to ft.
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. CDE 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 30 ft. to 62 ft., From ft. to ft., From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 13 ft. to 62 ft., From ft. to ft., From ft. to ft., From ft. to ft.

6) GROUT MATERIAL:

1 Neat cement	2 Cement grout	3 Bentonite	4 Other
---------------	----------------	-------------	---------

Grout Intervals: From 3 ft. to 13 ft., From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? EAST How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	24	Clay			
24	38	fine to med Sand			
38	62	Charcoal Shale			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-31-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 3186 This Water Well Record was completed on (mo/day/yr) 3-31-86 under the business name of Wenger Drill by signature [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.