

1) LOCATION OF WATER WELL: County: Sedgewick, NW 1/4 SW 1/4 SW 1/4 Section 7 Township Number T 28 S Range Number R 2 E 20

Distance and direction from nearest town or city street address of well if located within city: 1 W. 2 3/4 mi. Goodland KS.

2) WATER WELL OWNER: Eddie Hamilton

RR#, St. Address, Box #: Goodland KS 67052

City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4) DEPTH OF COMPLETED WELL: 96 ft. ELEVATION: 13 ft. below land surface measured on mo/day/yr 5-26-83.

Depth(s) Groundwater Encountered 1. 13 ft. 2. 58 ft. 3. 10 ft.

WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 5-26-83.

Pump test data: Well water was 58 ft. after 1/2 hours pumping 10 gpm

Est. Yield 15 gpm: Well water was 96 ft. after 10 hours pumping 10 gpm

Bore Hole Diameter 11 in. to 96 ft. and 10 in. to 10 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5) TYPE OF BLANK CASING USED: 1 Steel 2 RMP (SR) 3 Wrought iron 4 Concrete tile 5 Other (specify below) CASING JOINTS: Glued X Clamped

Blank casing diameter 5 in. to 17 ft. Dia 1 in. to 1 ft. Dia 1 in. to 1 ft. Dia

Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 17 ft. to 96 ft. From 17 ft. to 96 ft. From 17 ft. to 96 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 96 ft. From 13 ft. to 96 ft. From 13 ft. to 96 ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? West

How many feet? 130.

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-26-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-11-83 under the business name of Wminger Duller by (signature) Wminger Duller

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.