

1 LOCATION OF WATER WELL: County: Sedg Fraction: NE SE NW 1/4 1/4 1/4 Section Number: 17 Township Number: 28 Range Number: 2 E/W

Distance and direction from nearest town or city street address of well if located within city: 0.3 South of E Goddard St

2 WATER WELL OWNER: Craig PAGE RR#1 Goddard KS 67052 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Section Box Diagram]

4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 1818 ft. below land surface measured on mo/day/yr 1-31-85

WELL'S STATIC WATER LEVEL: 1818 ft. below land surface measured on mo/day/yr 1-31-85

Pump test data: Well water was 1818 ft. after 20 hours pumping 20 gpm

Est. Yield: 30 gpm: Well water was 1818 ft. after 20 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 36 ft. and 36 in. to 36 ft.

WELL WATER TO BE USED AS: 5 Public water supply 11 Injection well 12 Other (Specify below)

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. to 16 ft. Dia. 1 in. to 16 ft. Dia. 1 in. to 16 ft. Dia.

Casing height above land surface: 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 50R26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 16 ft. to 36 ft. From 16 ft. to 36 ft. From 16 ft. to 36 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 36 ft. From 13 ft. to 36 ft. From 13 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? NW How many feet? 90

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-31-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1518 This Water Well Record was completed on (mo/day/yr) 2-3-85 under the business name of Weninger Drilling by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	17	clay			
17	34	sand			
34	36	Shale			