

1 LOCATION OF WATER WELL: Fraction 1/4 SW 1/4 SE 1/4 NW 1/4 Section Number 17 Township Number 28 S Range Number 2 W

Distance and direction from nearest town or city street address of well if located within city? 2 So 1/4 E. Goddard KS

2 WATER WELL OWNER: Jean Fectel

RR#, St. Address, Box #: R 2 Goddard KS 67052

City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 51 ft. ELEVATION: 10-25-84

Depth(s) Groundwater Encountered 1. 16 ft. 2. 18 ft. 3. 20 ft.

WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 10-25-84

Pump test data: Well water was 18 ft. after 12 hours pumping 20 gpm

Est. Yield 25-35 gpm: Well water was 18 ft. after 12 hours pumping 20 gpm

Bore Hole Diameter 11 in. to 51 ft. and 11 in. to 51 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

Blank casing diameter 5 in. to 21 ft. Dia 1.59 lbs./ft. Wall thickness or gauge No. 50R-26

Casing height above land surface 12 in. weight 1.59

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 21 ft. to 51 ft. From 13 ft. to 51 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 51 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 200 ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? West

How many feet? 200

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 10-25-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on 11-8-84 under the business name of Wminger Pilling by (signature) J. M. Wminger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.