


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SW 1/4 SE 1/4	22	T 28 S	R 2W E/W
Distance and direction from nearest town or city street address of well if located within city? 5415 So. 157th St. West Clearwater, Ks.					
2 WATER WELL OWNER: Jim Curley RR#, St. Address, Box # : 3319 So. Fern City, State, ZIP Code : Wichita, Ks. Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 15 ft.			
		Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 4-16-85			
		Pump test data: Well water was 15 ft. after 15 hours pumping 15 gpm			
		Est. Yield 15 gpm: Well water was 15 ft. after 15 hours pumping 15 gpm			
		Bore Hole Diameter 14 in. to 14 in. to 14 in. to 14 in.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 <u>RMP (SR)</u> 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 2 PVC 4 <u>ABS</u> 6 Asbestos-Cement 9 Other (specify below) Welded X Cer-Mac styrene SDR-26 Threaded X					
Blank casing diameter 5 in. to 23 ft. Dia 5 in. to 23 ft. Dia 5 in. to 23 ft. Dia 5 in. to 23 ft.					
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 <u>RMP (SR)</u> 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) X 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) X					
SCREEN-PERFORATED INTERVALS: From 23 ft. to 40 ft. From 23 ft. to 40 ft. From 23 ft. to 40 ft. From 23 ft. to 40 ft.					
GRAVEL PACK INTERVALS: From 14 ft. to 40 ft. From 14 ft. to 40 ft. From 14 ft. to 40 ft. From 14 ft. to 40 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other X					
Grout intervals: From 4 ft. to 14 ft. From 4 ft. to 14 ft. From 4 ft. to 14 ft. From 4 ft. to 14 ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) None Apparent 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	16	Clay			
16	32	Fine Sand			
32	40	Grey Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-16-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-8-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					