

1 LOCATION OF WATER WELL: County: SEDGWICK NE 1/4 NE 1/4 NW 1/4 Section Number 23 Township Number 28 S Range Number 2 EW

Distance and direction from nearest town or city street address of well if located within city? 14711 W. 4TH

2 WATER WELL OWNER: SCOTT MCLEARY RR#, St. Address, Box #: 310 S. SHERMAN City, State, ZIP Code: WICHITA, KS 67213

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 61 ft. ELEVATION: 6-1-87

Depth(s) Groundwater Encountered: 1 35 ft. 2 35 ft. 3 12 ft.

WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on mo/day/yr 6-1-87

Pump test data: Well water was 35 ft. after 12 hours pumping 20 gpm

Est. Yield: 30 gpm: Well water was 35 ft. after 12 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 61 ft. and 11 in. to 61 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded

Blank casing diameter: 5 in. to 50 ft., Dia. 12 in. to 1.59 lbs./ft. Wall thickness or gauge No. SPR-26

Casing height above land surface: 12 in., weight 1.59

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut

SCREEN-PERFORATED INTERVALS: From 50 ft. to 61 ft. From 50 ft. to 61 ft. From 20 ft. to 61 ft. From 20 ft. to 61 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 61 ft. From 20 ft. to 61 ft. From 20 ft. to 61 ft. From 20 ft. to 61 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 20 ft. From 3 ft. to 20 ft. From 3 ft. to 20 ft. From 3 ft. to 20 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? SW How many feet? 130

FROM TO LITHOLOGIC LOG

0 2 Top soil

2 50 Clay

50 56 Sand

56 61 Shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-1-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-4-87 under the business name of WENINGER DRILLING by (signature) Jerome Weninger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.