

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 Section 32 Township 28 S Range 2 E
County: Sedgwick
Distance and direction from nearest town or city street address of well if located within city? 1 mile North of Clonell KS.
2 WATER WELL OWNER: Marty Maus
RR#, St. Address, Box #: 5136 S 183 W
City, State, ZIP Code: Viola KS 67149
Board of Agriculture, Division of Water Resources
Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 11 ft.
Depth(s) Groundwater Encountered: 11 ft. ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL: 11 ft. below land surface measured on mo/day/yr 1-29-92
Pump test data: Well water was 40 gpm ft. after 12 hours pumping 20 gpm
Est. Yield: 40 gpm Well water was 11 ft. after 12 hours pumping 20 gpm
Bore Hole Diameter: 11 in. to 65 ft. and in. to ft.
WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
3 Fiberglass Threaded
Blank casing diameter: 5 in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft. Dia.
Casing height above land surface: 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PRC
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 22 ft. to 65 ft. From ft. to ft. From ft. to ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 11 ft. to 65 ft. From ft. to ft. From ft. to ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 17 ft. From ft. to ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? Southeast How many feet? 100
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 10 clay
10 20 sand
20 65 shale
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-27-92 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-29-92
under the business name of Weinger Drilling Inc. by (signature) Susan K. Weinger
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.