


1 LOCATION OF WATER WELL: County: Nowa Fraction: SE 1/4 SE 1/4 SE 1/4 Section Number: 32 Township Number: T 28 S Range Number: R 20 EW

Distance and direction from nearest town or city street address of well if located within city?
2 1/2 W-1 S Mullinville Kansas

2 WATER WELL OWNER: Steve Brown Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: Mullinville Kans Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 137 ft. ELEVATION: 103 ft. below land surface measured on mo/day/yr 8-5-82
 Depth(s) Groundwater Encountered: 103 ft. 2. 103 ft. 3. 8-5-82 ft.
 WELL'S STATIC WATER LEVEL: 103 ft. below land surface measured on mo/day/yr 8-5-82
 Pump test data: Well water was 103 ft. after 1 hours pumping 5 gpm
 Est. Yield 1.5 gpm; Well water was 103 ft. after 1 hours pumping 5 gpm
 Bore Hole Diameter: 8 3/4 in. to 137 ft., and 137 in. to 137 ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF CASING USED:
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 117 ft., Dia 117 in. to 117 ft., Dia 117 in. to 117 ft.
 Casing height above land surface 12 in., weight 50 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 112 ft. to 137 ft., From 112 ft. to 137 ft., From 112 ft. to 137 ft.
 GRAVEL PACK INTERVALS: From 102 ft. to 137 ft., From 102 ft. to 137 ft., From 102 ft. to 137 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 14 ft., From 4 ft. to 14 ft., From 4 ft. to 14 ft.
 What is the nearest source of possible contamination:
 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? NW How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	TOP			
1	5	Silt & Sand			
5	16	Brown Clay			
16	62	Tan Clay			
62	85	Tan Clay + GRAVEL			
85	124	GRAVEL			
124	137	Gray Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-5-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 8-19-83 under the business name of Carl Hayes Water Well Serv. by (signature) Carl Hayes

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
28
R
20
EW
SEC.
32
SE 1/4
SE 1/4
SE 1/4
SE 1/4