


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		SE 1/4 SE 1/4 SE 1/4	1	T 28 S	R 21 E/W
Distance and direction from nearest town or city street address of well if located within city? From Ford - Kiowa County Line - 3 miles North					
2 WATER WELL OWNER:		WELL #1 - at correls			
RR#, St. Address, Box # :		Box 1297 Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Dodge City, Kansas 67801 Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 56 ft. below land surface measured on mo/day/yr 4-30-91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 80 in. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XX Clamped			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
Blank casing diameter 5 in. to 80 ft., Dia. in. to ft., Dia. in. to ft.		Casing height above land surface 12 in., weight 200 psi lbs./ft. Wall thickness or gauge No. SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 20 ft. to 80 ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite		Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination: none		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Top soil & fine sand			
20	40	Fine to medium sand			
40	60	Medium to coarse sand & small gravel			
60	75	Coarse w/medium sand to large gravel			
75	82	Rock layers			
82	100	Clay & red bed			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-23-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 6-3-91 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) <i>Joseph Cist</i>					