


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County FORD	Fraction NE NW SW 1/4 1/4 1/4	Section number 21	Township number T 28 S	Range number R 21 E/W
2. Distance and direction from nearest town or city: 2 3/4 N - 3/4 E OF BUCKLIN KS			3. Owner of well: KEITH KIRKPATRICK R.R. or street: BUCKLIN, KS 67834 City, state, zip code:			
4. Locate with "X" in section below: 			Sketch map:			
5. Type and color of material			From	To	6. Bore hole dia. 8 in. Completion date 3-26-82 Well depth 135 ft.	
top soil + clay			0	10	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
Sand			10	30	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Clay			30	50	9. Casing: Material PVC Height Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 30 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 2.9 lbs./ft. Dia. 5 in. to 135 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. SAR 21	
Sand and clay			50	80	10. Screen: Manufacturer's name Pearless Type PVC Dia. 5" Slot/gauze 115 Length 20' Set between 115 ft. and 135 ft. Gravel pack? Yes Size range of material 4x30% Fine	
Sand			80	135	11. Static water level: 80 ft. below land surface Date 3-26-82 mg./day/yr.	
Shale			135		12. Pumping level below land surfaces: N/A ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 50 g.p.m.	
					13. Water sample submitted: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Date	
					14. Well head completion: 30" Pitless adapter 30" Inches above grade	
					15. Well grouted? Yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
					16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
					17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
			(Use a second sheet if needed)			
18. Elevation:		19. Remarks: Banks Oil Co, 200 W Douglass Wichita KS 67602 OIL OPERATOR		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BRAU DRILL CO INC Business name BUCKLIN KS 2177 Address Signed [Signature] Date 3-26 Authorized representative		