


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford	NW 1/4 NE 1/4 NE 1/4	27	T 28 S	R 21 EW

Distance and direction from nearest town or city street address of well if located within city?

2 miles north 2 miles east of Bucklin

2 WATER WELL OWNER: Perry Staats	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : RR	Application Number:
City, State, ZIP Code : Bucklin Kansas 67834	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 159 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 92 ft. 2. 92 ft. 3. 92 ft.
	WELL'S STATIC WATER LEVEL 92 ft. below land surface measured on mo/day/yr 5/9/89
	Pump test data: Well water was 100 gpm: Well water was 100 gpm
	Bore Hole Diameter 8 3/4 in. to 159 ft., and 159 ft. to 159 ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
☒ 2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 5 in. to 139 ft., Dia 139 in. to 139 ft., Dia 139 in. to 139 ft.			
Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. SDR-26			
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	☒ 8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 139 ft. to 159 ft., From 139 ft. to 159 ft., From 139 ft. to 159 ft.			
GRAVEL PACK INTERVALS: From 25 ft. to 159 ft., From 25 ft. to 159 ft., From 25 ft. to 159 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ 3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 25 ft., From 4 ft. to 25 ft., From 4 ft. to 25 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
☒ 1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well? Northwest	How many feet? 100			

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	35	Tan clay			
35	47	Sand			
47	80	Tan clay			
80	97	Sand & clay streaks			
97	100	Tan clay			
100	115	Sand			
115	117	Tan Clay			
117	120	Sand			
120	154	Gravel			
154		Tan clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/9/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 8/14/89 under the business name of Carl Hayse Water Well Service by (signature) Carl Hayse
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send to three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.