WATE	ER WI	ELL RECORD	Form V	VWC-5	ī	Division of Water	Resources App. N	20150398	
		N OF WATER WELL:	Fraction			tion Number		Range Number	
County: Ford 1/4 SE			1/4 SE 1/4 N	W ¼ NE		21	T 28 S	R 21 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .						Latitude: .37.599496 (in decimal degrees)			
3 N	lorth, 3	4 East of Bucklin			Lon	gitude: <u>099.61</u>	8637	(in decimal degrees)	
						vation:			
2 WATER WELL OWNER: Vincent Oil					Coll	Elevation:			
RR#, Street Address, Box #: 155 N. Market- Ste 700						GPS unit (Make/Model:)			
City, State, ZIP Code : Wichita, KS 67202						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
3 LOCATE WELL						Accuracy: <	3 m, 🔲 3-5 m, 🔲	5-15 m, >15 m	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 135 ft.									
SECTION BOX: Depth(s) Groundwater Encountered (1) ft (2)								2) 0	
WELL'S STATIC WATER LEVEL 92 ft. below land surface measured on mo/day/yr. 12-7-15. Pump test data: Well water was ft. after hours pumping gpm EST. YIELD N/A gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to .135 ft., and in. to								3) II. av/ur 12-7-15	
								ning gnm	
								nina	
								ft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
SW- SE- Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
Irrigation									
was a chemical/bacteriological sample submitted to Department? Yes V No									
S If yes, mo/day/yr sample was submitted									
5 TYPE OF CASING USED: Steel PVC Other									
Casing diameter 5 in to 9 Diameter in to 9 Diameter in to 9									
Casing neight above land surface in Weight SDR-20 lbs/ft Wall thickness or gauge No.									
THE OF SCREEN OR PERFORATION MATERIAL:									
Steel Stainless Steel PVC Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot									
Louvered shutter Key punched Wire wranged Wise wranged Other (opening)									
SCREEN-PERFORATED INTERVALS: From 135 ft. to95 ft., From ft. to95									
GRAVEL PACK INTERVALS: From								•	
								.o	
From the from the first th									
Grout Intervals: From ft. to ft., From 20 ft., From ft. to ft.									
What is the nearest source of possible contamination:									
what is the hearest source of possible contamination:									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							r (specify below)		
	Watertig	ht sewer lines	Feedvard	Fertilizer :	storage	Oil well/gas	well None		
Direc	tion from	n well			from w	ell	· · · · · · · · · · · · · · · · · · ·	• • • • • • • • • • • • • • • • • • • •	
FROM	TO	LITHOLOGIC	C LOG	FROM	TO		G (cont.) <u>or</u> PLU(GGING INTERVALS	
0 3	3 16	Top soil		130	135	Blue shale			
16		Soft, sandy clay							
10	18 Gravel- fine to small with								
18	clay streaks 69 Soft, sandy clay								
69	85			···					
85	110	Small gravel w/ clay streaks Gravel- small to med							
110	116	Small gravel w/ cemented sand							
116	129	Blue shale							
129 130 Ironated rock									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
under my jurisdiction and was completed on (mo/day/year) .12-7-15									
National Water Well Contractor S License (NO. 194 Interview Well Record was completed on (mag/day/see) 12-72-15									
under the business name of (Sectionality Defins Ent Inc.									
AND INCULTIONS. USE LYDEWINET OF DRIFT DEBT PLEASE PRESS FIDAL V and DDDIT along the Discussion of the Control									
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html									
			- Engl						