


1 LOCATION OF WATER WELL: County: Ford	Fraction <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 11	Township Number T <u>28</u> S	Range Number R 22 E/W
---	--	----------------------	----------------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

4 Miles East of Ford, Kansas

2 WATER WELL OWNER: Ford Land & Cattle	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Highway 154	Application Number:
City, State, ZIP Code: Ford, KS 67842	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 98' ft. ELEVATION: 33' ft.
	Depth(s) Groundwater Encountered 1. 33' ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 33' ft. below land surface measured on mo/day/yr
	Pump test data: Well water was 65' ft. after 3 hours pumping 525 gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 36 in. to 98' ft. and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 16 in. to 58 in. Dia			11 Other (specify)
Casing height above land surface 18 in. weight lbs./ft. Wall thickness or gauge No.			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 58" ft. to 98' ft.		
GRAVEL PACK INTERVALS:	From 98' ft. to 20' ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 2 Top Soil	
2 22 Sandy Silt	
22 30 Tan and White Clay	
30 56 Coarse Sand Fine to Medium Gravel	
56 90 Fine to Coarse Sand	
90 106 Tan and White Clay	
106 120 Blue Shale	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-19-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 514 This Water Well Record was completed on (mo/day/yr) 6-3-91 under the business name of by (signature) <i>Ernest Miller</i>
