


WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		NW 1/4 NE 1/4 NW 1/4	26	T 28 S	R 22 E/W
Distance and direction from nearest town or city street address of well, if located within city? 4W 2N. of Bucklin Kansas					
WATER WELL OWNER: Max Seacat					
City, State, ZIP Code: Bucklin Kansas					
Board of Agriculture, Division of Water Resources					
Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 146 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 114 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 114 ft. below land surface measured on mo/day/yr 5-11-78			
		Pump test data: Well water was 114 ft. after 1 hours pumping 3 gpm			
		Est. Yield 20 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 3/4 in. to 14 1/2 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Pasture			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel		Welded			
2 PVC		Threaded			
3 RMP (SR)					
4 ABS					
5 Wrought iron					
6 Asbestos-Cement					
7 Fiberglass					
8 Concrete tile					
9 Other (specify below)					
Blank casing diameter 5 in. to 12 1/2 ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 15 lbs./ft. Wall thickness or gauge No. 200					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		7 PVC			
2 Brass		10 Asbestos-cement			
3 Stainless steel		11 Other (specify)			
4 Galvanized steel		12 None used (open hole)			
5 Fiberglass		8 RMP (SR)			
6 Concrete tile		9 ABS			
SCREEN OR PERFORATION OPENINGS ARE:		10 Saw cut 11 None (open hole)			
1 Continuous slot		9 Drilled holes			
2 Louvered shutter		10 Other (specify)			
3 Mill slot					
4 Key punched					
5 Gauzed wrapped					
6 Wire wrapped					
7 Torch cut					
SCREEN-PERFORATED INTERVALS:					
From 126 ft. to 146 ft., From ft. to ft.					
GRAVEL PACK INTERVALS:					
From 110 ft. to 146 ft., From ft. to ft.					
GROUT MATERIAL:					
1 Neat cement		2 Cement grout			
3 Bentonite		4 Other			
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		10 Livestock pens			
2 Sewer lines		11 Fuel storage			
3 Watertight sewer lines		12 Fertilizer storage			
4 Lateral lines		13 Insecticide storage			
5 Cess pool		14 Abandoned water well			
6 Seepage pit		15 Oil well/Gas well			
7 Pit privy		16 Other (specify below)			
8 Sewage lagoon		Passing Cattle			
9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	68	Clay			
68	74	Sand			
74	112	Clay			
112	146	Gravel			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-11-78 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 5-11-78					
Under the business name of Carl Kayse Water Well Serv. by (signature) Carl Kayse					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					