


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 30 Township Number T 28 S Range Number R 22 E/W
 County: FORD

Distance and direction from nearest town or city street address of well if located within city?

3 N 1 W 1/4 N. Kingsdown Kans

2 WATER WELL OWNER: Kenneth McCarty Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: Kingsdown Kansas Application Number:
 City, State, ZIP Code:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 17.5 ft. ELEVATION: 9-10-83
 Depth(s) Groundwater Encountered 1 17.8 ft. 2 17.8 ft. 3 17.8 ft.
 WELL'S STATIC WATER LEVEL 17.8 ft. below land surface measured on mo/day/yr 9-10-83
 Pump test data: Well water was 17.8 ft. after 1 hours pumping 15 gpm
 Est. Yield 15 gpm; Well water was 17.8 ft. after 1 hours pumping 15 gpm
 Bore Hole Diameter 8 3/4 in. to 2.00 ft., and 2.00 in. to 2.00 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped X Welded X Threaded X
 Blank casing diameter 5 in. to 17.5 ft. Dia 5 in. to 17.5 ft. Dia 5 in. to 17.5 ft. Dia 5 in. to 17.5 ft.
 Casing height above land surface 1.2 in., weight 5.25 lbs./ft. Wall thickness or gauge No. 5DR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 12.5 ft. to 19.5 ft. From 12.5 ft. to 19.5 ft. From 12.5 ft. to 19.5 ft. From 12.5 ft. to 19.5 ft.
 GRAVEL PACK INTERVALS: From 16.0 ft. to 19.5 ft. From 16.0 ft. to 19.5 ft. From 16.0 ft. to 19.5 ft. From 16.0 ft. to 19.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Neat cement
 Grout Intervals: From 4 ft. to 14 ft. From 4 ft. to 14 ft. From 4 ft. to 14 ft. From 4 ft. to 14 ft.
 What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? NE How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	Top Soil			
1	110	Tan Clay			
110	120	Sand with Clay			
120	182	Tan Clay			
182	186	Gravel			
186	189	Clay			
189	192	Gravel			
192	195	Clay			
195	200	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-10-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 7-22-84 under the business name of Carl Hays Water Well Serv. by (signature) Carl Hays
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.