

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number																
COUNTY: FORD		SE 1/4 NW 1/4 NE 1/4	10	T 28 S	R 23 E																
Distance and direction from nearest town or city street address of well if located within city? FROM FORD, KS. 3 W ON FORD & ENSIGN ROAD & 1 MILE SOUTH																					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources																			
DROSTE, JERRY		Application Number:																			
RR#, St. Address, Box #: 2420 HART AVE.																					
City, State, ZIP code: DODGE CITY, KS 67801-																					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 115 ELEVATION: 0																			
<div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 5px;">1 mile</div> <table border="1" style="border-collapse: collapse; text-align: center;"> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td>NW</td><td>NE</td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td>SW</td><td>SE</td><td> </td></tr> </table> </div>							NW	NE							SW	SE		Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.			
			NW	NE																	
			SW	SE																	
WELL'S STATIC WATER LEVEL 66 ft. below land surface measured on mo/day/yr 12/23/94																					
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm																					
Estimated Yield 25 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm																					
Bore Hole Diameter 9 in. to 115 ft., and in. to 0 ft.																					
WELL WATER TO BE USED AS: DOMESTIC																					
Was a chemical/bacteriological sample submitted to department? No ;																					
If yes, mo/day/yr sample was submitted Water well disinfected? Yes																					
5 TYPE OF BLANK CASING USED: PVC		CASING JOINTS: GLUED																			
Blank casing diameter 5 in. to 115 ft., Dia		in. to 0 ft., Dia in. to 0 ft.																			
Casing height above land surface 12 in.,		weight 200 lbs/ft. Wall thickness or gauge No. 21																			
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC																					
SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																					
SCREEN PERFORATED INTERVALS:		From 90 ft. to 110 ft., From 0 ft. to 0 ft.																			
GRAVEL PACK INTERVALS:		From 0 ft. to 0 ft., From 0 ft. to 0 ft.																			
		From 25 ft. to 115 ft., From 0 ft. to 0 ft.																			
		From 0 ft. to 0 ft., From 0 ft. to 0 ft.																			
6 GROUT MATERIAL BENTONITE																					
Grout Intervals: From 0 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.																					
What is the nearest source of possible contamination: NONE - NEW SITE																					
Direction from well?		How many feet? 0																			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																
0	55	TOPSOIL CLAY																			
55	60	SAND GRAVEL																			
60	80	CLAY																			
80	112	SAND GRAVEL																			
112	115	CLAY																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 12/23/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 02/07/95 under the business name of JOB'S WELL SERVICE, INC. by (signature) Judith Cist																					