(M)

(SA 82a-1212 LOCATION OF WATER WELL: Section Number Township Number Range Number 20 28 R 23 Distance and direction from nearest town or city street address of well if located within city? 8N+ ZE From Bloom 2 WATER WELL OWNER: J. ... RR#, St. Address, Box # : Board of Agriculture, Division of Water Resources City, State, ZIP Code : Dodge City, KS 6780 Application Number: 120 ft. ELEVATION: AN "X" IN SECTION BOX: WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs sample was sub-Water Well Disinfected? Yes TYPE OF BLANK CASING USED: CASING JOINTS: Glued Clamped 5 Wrought iron 8 Concrete tile 1 Steel 9 Other (specify below) 3 RMP (SR) 6 Asbestos-Cement Welded PVC 7 Fiberglass Threaded..... Blank casing diameter 5. in. to 8.0 ft., Dia in. to ft., Dia i TYPE OF SCREEN OR PERFORATION MATERIAL: 🕭 PVC 10 Asbestos-Cement 11 Other (Specify) 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) 2 Brass 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 7 Torch cut 10 Other (specify)ft 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS:
 From
 ft. to
 ft., From
 ft. to
 ft.

 From
 2.0
 ft. to
 1.20
 ft., From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: 2 Cement grout 4 Other..... **GROUT MATERIAL:** 1 Neat cement Bentonite Grout Intervals: From #p ft. to 20 ft., From ft. to ft. to ft. from ft. from ft. What is the nearest source of possible contamination: 10 Livestock pens Abandoned water well 11 Fuel storage 1 Septic tank 4 Lateral lines 7 Pit privy 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? A/ = How many feet? Zcoc FROM TO LITHOLOGIC LOG FROM PLUGGING INTERVALS Ø 15 15 50 tan clay somel + orave かひ ize der the business name of Batel (LOCO) 11. in Inc. by (signature) Bothe Batel Batel Bothe B

and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your

records. Fee of \$5.00 for each constructed well.

(M)

KSA 82a-1212 LOCATION OF WATER WELL: Section Number Township Number Range Number 20 28 R 23 Distance and direction from nearest town or city street address of well if located within city? 8N+ ZE from Bloom 2 WATER WELL OWNER: J. RR#, St. Address, Box # : Board of Agriculture, Division of Water Resources City, State, ZIP Code : Dodge City, KS 6780

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL Application Number: 120 ft. ELEVATION: AN "X" IN SECTION BOX: - NE WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs sample was sub-Water Well Disinfected? Yes TYPE OF BLANK CASING USED: CASING JOINTS: Glued Clamped 5 Wrought iron 8 Concrete tile 1 Steel 9 Other (specify below) 3 RMP (SR) 6 Asbestos-Cement Welded PVC 7 Fiberglass Threaded..... Blank casing diameter 5. in to 8.0 ft., Dia in to ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 🕭 PVC 10 Asbestos-Cement 11 Other (Specify) 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) 2 Brass 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 7 Torch cut 10 Other (specify)ft 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS:
 From
 ft. to
 ft., From
 ft. to
 ft.

 From
 2.0
 ft. to
 ft., From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: 2 Cement grout 4 Other..... **GROUT MATERIAL:** 1 Neat cement Bentonite Grout Intervals: From #p ft. to 20 ft., From ft. to ft. to ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens Abandoned water well 11 Fuel storage 15 Oil well/Gas well 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? ME How many feet? Zcoc FROM TO LITHOLOGIC LOG FROM PLUGGING INTERVALS Ø 15 15 50 tan clay somel + orave 50 izo der the business name of Batel (LOCO) In large l and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your

records. Fee of \$5.00 for each constructed well.